



Extruded Brackets -for 1-slot-

-Slot Type: HFS5 Series (Aluminum Frames 20-25-40 Square)-







Part Number	Mass (g)	Applicable Screw · T Nut				Allowable	€ Unit Price	Volume Discount	
Part Number	IVIASS (9)	Screw	Qty.	T Nut	Qty.	Load (N)	1~99 pcs.	100~	
HBKTST5									
HBKTS5	15	CBM5-10	2	HNTT5-5	2				
HBKTSB5						833			
(Black Anodize)									

^{*} For repairing black anodizing, refer to P.748


Features: Aluminum Extruded Brackets. Excels in appearance.



Part Number	Mass	Applicable Screw · T Nut				Allowable Load	€ Unit Price	Volume Discount	
Part Number	(g)	Screw	Qty.	T Nut	Qty.	(N)	1~99 pcs.	100~	
HBLTS5		CBM5-10		HNTT5-5					
HBLTS5-4 (For M4 Bolt)		CBM4-10		HNTT5-4					
HBLTSB5* (Black Anodize)	2 HNTT5-5 2 4] _	833			
CHBLTS5 (Clear Coating)		633							
HBLTV5									
HBLTVB5* (Black Anodize)									



Features: Numbers of screws are the same as HBKTS8. Extrusions can be connected more securely.




	Part Number	Mass (g)	App Screw	licable S Qty.	crew · T Nut T Nut	Qty.	Allowable Load (N)	€ Unit Price 1~99 pcs.	Volume Discount 100~
- 1	HBKUS5								
ī	HBKUSB5	31	CBM5-14	2	HNTT5-5	2	833		
((Black Anodize)								

Features: Numbers of screws are the same as HBLTS8-45. Extrusions can be connected more securely.




HBLUS5 EN AC-51400/ ALMGSI0,7-T5 Anodize	Туре	M Material	Surface Treatment
	HBLUS5		Anodize




Allowable Load (N)

Features: Hole positions are eccentric. Can be combined with plates of 5mm and 3mm thickness when using taps for mounting covers.




Part	Mass	Applicable Screw · T Nut				Allowable Load	€ Unit Price	Volume Discount		
Number	(g)	Screw	Qty.	T Nut	Qty.	(N)	1~99 pcs.	100~		
HBLTH5										
HBLTHB5* (Black Anodize)	15	CBM5-10	2	HNTT5-5	2	833				



CAD Data


* For repairing black anodizing, refer to P.748

Features: Extruded Brackets with twice as many screws. Extrusions can be connected more securely.



Part Number	Mass (g)	Applicable Screw · I Nut			Allowable Load (N)	€ Unit Price	volume Discount	
Part Number	Iviass (g)	Screw	Qty.	T Nut	Qty.	Allowable Load (N)	1~99 pcs.	100~
HBLTSW5	26	CBM5-10	4	HNTT5-5	4	1176		
HBLTVW5	36	CDIVID-10	4	питто-о		1170		

Features: Extruded Brackets Unequal Sides. Effective when strength is required in the narrow clearances between extrusions.



Part	Mass	Applica	ble S	crew · T Nu	t	Allowable	€ Unit Price	Volume Discount	
Number	(g)	Screw	Qty.	T Nut	Qty.	Load (N)	1~99 pcs.	100~	
HBITE5	21	CBM5-10	3	HNTT5-5	3	1004			



Alterations	Code	Spec.	Applicable Brackets	Price Adder	
			HBLTS5 HBLTS5-4	0,30	
	İ		CHBLTS5	0,50	
		Adds taps on a	HBLTV5	0.40	
Mounting Holes for Cover			HBLTVB5	0,40	
		bracket for cover mounting. (M5 on Both Sides)	HBLUS5		
			HBKTS5		
			HBKUS5		
		(Mounting screw	HBLUS5	0,30	
		P.644 HCBM)	HBLTH5		
		F.O44 HODIVI)	HBLTHB5]	
			HBLTSW5		
			HBLTVW5	0,40	
			HBLTF5	0.30	

	Alterations	Code		Spec.		Applicable Brackets			Pric	ce Ac	lder		
_		SET	Supplies	a set of appl	icable	ĺ	SET	SST	SEU	SSU	SEP	SSP	SEC
		(Stainless Steel)		and nuts for fi	HBLTS5	0.82	0.60	1.06	1.64	1.06	4.04	1.24	
J		SEU	bracket t	to a extrusion	HBLTS5-4	0,02	0,60	1,06	1,64	1,06	1,24	1,24	
		(Pre-assy.	(Adds to	the bracket p	orice)	HBLTSB5	0,87	-	1,11	-	1,11		-
		Insertion Spring Nuts) SSU				CHBLTS5	0.00	0.00	4.00	4.04	4.00	1.24	1.24
						HBLTV5	0,82	0,60	1,06	1,64	1,06	1,24 1	1,24
		(Pre-assy. Insertion Spring			HBLTVB5	0,87	-	1,11	-	1,11		-	
	Applicable	Nuts Stainless	(Ex.) When HBLTS5 is specified,	,	HBKTST5		0.00	1.06	1.64				
	Screws	Steel)	Code	Screws	Nuts	HBKTS5	0,82	0,60	1,06	1,64	1,06	1,24	1,24
	and Nuts	SEP (Deat Asset)	SEI	CBM5-10 SCB5-10	HNTT5-5 HNTTBS5-5	HBKTSB5	0,87	-	1,11	-	1,11		-
	a set.	(Post-Assy.	SFU	CBM5-10	HNTU5-5	HBLUS5							
		Spring Nuts)	SSU	SCB5-10	SHNTU5-5	HBKUS5	0,84	0,60	1,08	1,64	1,08	1,24	1,28
		(Pre-assy. Insertion Spring	SEP	CBM5-10	HNTP5-5	HBKUSB5	0,89	-	1,13	-	1,13		-
			SSP	SCB5-10	SHNTP5-5	HBLTH5	0,82	0,60	1,06	1,64	1,06	1,24	1,24
		Nuts	SEC	HCBST5-12	HNTT5-5	HBLTHB5	0,87	-	1,11	-	1,11		-
		Stainless Steel)	When specifying other than HBLTS5, check for the			HBLTSW5							
		(Captured Washer		applicable screws and nuts.		HBLTVW5	1,64	1,20	2,12	3,28	2,12	2,48	-
		Screws Nuts)			HBLTF5	1,23	90	1,62	2,46	1,62	1,86	1,86	

©Screws for black anodized parts are HCBMTB (Trivalent Chromate Black). **P.641** ©When -SET, -SEU or -SEP is specified, it is not RoHS compliant.

^{*} For repairing black anodizing, refer to P.748