



FAG

★ B71919-C-T-P4S-UL

Spindle bearing

Schaeffler ID:
0191547550000

★ Preferred product

Spindle bearings B719..-C, adjusted,
in pairs or sets, contact angle $\alpha = 15^\circ$,
restricted tolerances

Technical information



Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	100 °C	Operating temperature max.
	0,572 kg	Weight

Main Dimensions & Performance Data

d	95 mm	Bore diameter
D	130 mm	Outside diameter
B	18 mm	Width
C_r	48.500 N	Basic dynamic load rating, radial
C_{0r}	36.500 N	Basic static load rating, radial
C_{ur}	3.650 N	Fatigue load limit, radial
$n_{G \text{ Grease}}$	10.000 1/min	Limiting speed for grease lubrication
$n_{G \text{ Oil}}$	16.000 1/min	Limiting speed for oil lubrication

Dimensions

r_{\min}	1,1 mm	Minimum chamfer dimension
$r_{1 \min}$	1,1 mm	Minimum chamfer dimension
α	15 °	Contact angle



Mounting dimensions

d_a	102 mm	Diameter shaft shoulder
d_a	h12	Diameter shaft shoulder clearance
D_a	124 mm	Shoulder diameter outer ring
D_a	H12	Shoulder diameter outer ring clearance
$r_{a \max}$	0,6 mm	Maximum recess radius
$r_{a1 \max}$	0,6 mm	Maximum recess radius
$E_{tk \min}$	105,9 mm	Minimum diameter injection pitch
$E_{tk \max}$	109,2 mm	Maximum diameter injection pitch
$E_{tk1 \min}$	105,9 mm	Minimum diameter injection pitch
$E_{tk1 \max}$	109,2 mm	Maximum diameter injection pitch
a	24,1 mm	Distance between the apexes of the pressure cones

Additional information

F_{VL}	243 N	Preload force light
F_{VM}	813 N	Preload force medium
F_{VH}	1.651 N	Preload force heavy
K_{aEL}	743 N	Lift-off force light
K_{aEM}	2.679 N	Lift-off force medium
K_{aEH}	5.806 N	Lift-off force heavy
c_{aL}	84,4 N/ μm	Axial rigidity light
c_{aM}	144 N/ μm	Axial rigidity medium
c_{aH}	206 N/ μm	Axial rigidity heavy