



FAG

## ★ B71932-C-T-P4S-UL

Spindle bearing

Schaeffler ID:  
0191553790000

★ Preferred product

Spindle bearings B719...-C, adjusted,  
in pairs or sets, contact angle  $\alpha = 15^\circ$ ,  
restricted tolerances

## Technical information



## Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	100 °C	Operating temperature max.
	2,587 kg	Weight

## Main Dimensions &amp; Performance Data

d	160 mm	Bore diameter
D	220 mm	Outside diameter
B	28 mm	Width
$C_r$	128.000 N	Basic dynamic load rating, radial
$C_{0r}$	106.000 N	Basic static load rating, radial
$C_{ur}$	8.100 N	Fatigue load limit, radial
$n_{G \text{ Grease}}$	6.000 1/min	Limiting speed for grease lubrication
$n_{G \text{ Oil}}$	9.000 1/min	Limiting speed for oil lubrication

## Dimensions

$r_{\min}$	2 mm	Minimum chamfer dimension
$r_{1 \min}$	1 mm	Minimum chamfer dimension
$\alpha$	15 °	Contact angle



### Mounting dimensions

$d_a$	170 mm	Diameter shaft shoulder
$d_a$	h12	Diameter shaft shoulder clearance
$D_a$	209 mm	Shoulder diameter outer ring
$D_a$	H12	Shoulder diameter outer ring clearance
$r_{a \max}$	1 mm	Maximum recess radius
$r_{a1 \max}$	1 mm	Maximum recess radius
$E_{tk \min}$	179,5 mm	Minimum diameter injection pitch
$E_{tk \max}$	184,7 mm	Maximum diameter injection pitch
$E_{tk1 \min}$	179,5 mm	Minimum diameter injection pitch
$E_{tk1 \max}$	184,7 mm	Maximum diameter injection pitch
$a$	39,5 mm	Distance between the apexes of the pressure cones

### Additional information

$F_{VL}$	722 N	Preload force light
$F_{VM}$	2.304 N	Preload force medium
$F_{VH}$	4.619 N	Preload force heavy
$K_{aEL}$	2.209 N	Lift-off force light
$K_{aEM}$	7.572 N	Lift-off force medium
$K_{aEH}$	16.164 N	Lift-off force heavy
$c_{aL}$	145 N/ $\mu$ m	Axial rigidity light
$c_{aM}$	243 N/ $\mu$ m	Axial rigidity medium
$c_{aH}$	344 N/ $\mu$ m	Axial rigidity heavy