



FAG

★ B7218-C-T-P4S-UL

Spindle bearing

Schaeffler ID:
0191572230000

★ Preferred product

Spindle bearings B72...-C, adjusted, in pairs or sets, contact angle $\alpha = 15^\circ$, restricted tolerances

Technical information



Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	100 °C	Operating temperature max.
	2,154 kg	Weight

Main Dimensions & Performance Data

d	90 mm	Bore diameter
D	160 mm	Outside diameter
B	30 mm	Width
C_r	125.000 N	Basic dynamic load rating, radial
C_{0r}	75.000 N	Basic static load rating, radial
C_{ur}	7.100 N	Fatigue load limit, radial
$n_{G \text{ Grease}}$	8.500 1/min	Limiting speed for grease lubrication
$n_{G \text{ Oil}}$	14.000 1/min	Limiting speed for oil lubrication

Dimensions

r_{\min}	2 mm	Minimum chamfer dimension
$r_{1 \min}$	2 mm	Minimum chamfer dimension
α	15 °	Contact angle



Mounting dimensions

d_a	104 mm	Diameter shaft shoulder
d_a	h12	Diameter shaft shoulder clearance
D_a	147 mm	Shoulder diameter outer ring
D_a	H12	Shoulder diameter outer ring clearance
$r_{a \max}$	2 mm	Maximum recess radius
$r_{a1 \max}$	1 mm	Maximum recess radius
$E_{tk \min}$	112,1 mm	Minimum diameter injection pitch
$E_{tk \max}$	120 mm	Maximum diameter injection pitch
$E_{tk1 \min}$	112,1 mm	Minimum diameter injection pitch
$E_{tk1 \max}$	120 mm	Maximum diameter injection pitch
a	31,8 mm	Distance between the apexes of the pressure cones

Additional information

F_{VL}	732 N	Preload force light
F_{VM}	2.280 N	Preload force medium
F_{VH}	4.513 N	Preload force heavy
K_{aEL}	2.267 N	Lift-off force light
K_{aEM}	7.640 N	Lift-off force medium
K_{aEH}	16.156 N	Lift-off force heavy
c_{aL}	109 N/ μ m	Axial rigidity light
c_{aM}	183 N/ μ m	Axial rigidity medium
c_{aH}	260 N/ μ m	Axial rigidity heavy