





FAG

HS7001-E-T-P4S-UL

Angular contact ball bearing

Schaeffler ID:
0385474060000Spindle bearings HS70..-E, adjusted,
in pairs or sets, contact angle $\alpha = 25^\circ$,
restricted tolerances

Technical information

**Temperature range**


T_{\min}	-30 °C	Operating temperature min.
T_{\max}	100 °C	Operating temperature max.
	23 g	Weight

Main Dimensions & Performance Data

d	12 mm	Bore diameter
D	28 mm	Outside diameter
B	8 mm	Width
C_r	2.320 N	Basic dynamic load rating, radial
C_{0r}	910 N	Basic static load rating, radial
C_{ur}	97 N	Fatigue load limit, radial
$n_{G \text{ Grease}}$	75.000 1/min	Limiting speed for grease lubrication
$n_{G \text{ Oil}}$	110.000 1/min	Limiting speed for oil lubrication

Dimensions

r_{\min}	0,3 mm	Minimum chamfer dimension
$r_{1 \min}$	0,3 mm	Minimum chamfer dimension
α	25 °	Contact angle



Mounting dimensions

d_a	16,5 mm	Diameter shaft shoulder
d_a	h12	Diameter shaft shoulder clearance
D_a	24,5 mm	Shoulder diameter outer ring
D_a	H12	Shoulder diameter outer ring clearance
$r_{a \max}$	0,3 mm	Maximum recess radius
$r_{a1 \max}$	0,1 mm	Maximum recess radius
$E_{tk \min}$	18,4 mm	Minimum diameter injection pitch
$E_{tk \max}$	18,9 mm	Maximum diameter injection pitch
$E_{tk1 \min}$	17,3 mm	Minimum diameter injection pitch
$E_{tk1 \max}$	18,9 mm	Maximum diameter injection pitch
a	8,7 mm	Distance between the apexes of the pressure cones

Additional information

F_{VL}	15 N	Preload force light
F_{VM}	44 N	Preload force medium
F_{VH}	88 N	Preload force heavy
K_{aEL}	43 N	Lift-off force light
K_{aEM}	131 N	Lift-off force medium
K_{aEH}	268 N	Lift-off force heavy
c_{aL}	26,7 N/ μm	Axial rigidity light
c_{aM}	40 N/ μm	Axial rigidity medium
c_{aH}	52,6 N/ μm	Axial rigidity heavy