

Technical information







Cylindrical roller bearing N2..-E-TVP, with cage, single row, non-locating bearing, 0 ribs on outer ring, 2 rib on inner ring, type

Temperature range

| T _{min} | -30 °C | Operating temperature min. | |
|------------------|----------|----------------------------|--|
| T _{max} | 120 °C | Operating temperature max. | |
| | 0,004 kg | Weight | |

Main Dimensions & Performance Data

| d | 40 mm | Bore diameter |
|-----------------------|--------------|---------------------------------------|
| D | 80 mm | Outside diameter |
| В | 18 mm | Width |
| C _r | 63.000 N | Basic dynamic load rating, radial |
| C _{Or} | 53.000 N | Basic static load rating, radial |
| C _{ur} | 8.500 N | Fatigue load limit, radial |
| n _{G Grease} | 9.300 1/min | Limiting speed for grease lubrication |
| n _{G Oil} | 10.900 1/min | Limiting speed for oil lubrication |
| | | |

Dimensions

| r _{1 min} | 1,1 mm | Minimum chamfer dimension |
|--------------------|---------|-----------------------------|
| s ₁ | 1 mm | Axial displacement |
| E | 71,5 mm | Raceway diameter outer ring |

Mounting dimensions

| d _{a min} | 47 mm | Minimum diameter shaft shoulder |
|---------------------|-------|--------------------------------------|
| D _{a max} | 73 mm | Maximum diameter of housing shoulder |
| r _{a1 max} | 1 mm | Maximum recess radius |

02.06.2021, 01:55:10 (GMT+08:00)



The datasheet is only an overview of dimensions and basic load ratings of the selected product. Please always observe all further information and guidelines for this product. For further information you can use the contact form on our website.