



FAG

★ NU1032-XL-M1

Cylindrical roller bearing

Schaeffler ID:
0167373180000

★ Preferred product

Cylindrical roller bearing NU.-XL-M1, with cage, single row, non-locating bearing, 2 ribs on outer ring, 0 ribs on inner ring (smooth), type NU

X-life

Technical information

Temperature range

T_{min}	-30 °C	Operating temperature min.
T_{max}	150 °C	Operating temperature max.
	5,805 kg	Weight

Main Dimensions & Performance Data

d	160 mm	Bore diameter
D	240 mm	Outside diameter
B	38 mm	Width
C_r	290.000 N	Basic dynamic load rating, radial
C_{0r}	355.000 N	Basic static load rating, radial
C_{ur}	44.000 N	Fatigue load limit, radial
n_G	4.650 1/min	Limiting speed
n_{gr}	3.000 1/min	Reference speed

Dimensions

r_{min}	2,1 mm	Minimum chamfer dimension
$r_{1 min}$	1,5 mm	Minimum chamfer dimension
s	4,3 mm	Axial displacement
E	220 mm	Raceway diameter outer ring
F	180 mm	Raceway diameter inner ring
$D_{1 min}$	212,9 mm	Minimum rib diameter outer ring

Mounting dimensions

$d_{a min}$	168 mm	Minimum diameter shaft shoulder
$d_{a max}$	178 mm	Maximum diameter of shaft shoulder
$d_{b min}$	184 mm	Minimum shaft shoulder
$D_{a max}$	230 mm	Maximum diameter of housing shoulder
$r_{a max}$	2,1 mm	Maximum recess radius
$r_{a1 max}$	1,5 mm	Maximum recess radius



