



FAG


## 31308-XL

Tapered roller bearing

Schaeffler ID:  
0804197980000Tapered roller bearings 313, main  
dimensions to DIN ISO 355 / DIN 720,  
separable, adjusted or in pairs

X-life

## Technical information



## Main Dimensions &amp; Performance Data

d	40 mm	Bore diameter
D	90 mm	Outside diameter
B	23 mm	Width, inner ring
C	17 mm	Width, outer ring
T	25,25 mm	Width, total
$C_r$	89.000 N	Basic dynamic load rating, radial
$C_{0r}$	83.000 N	Basic static load rating, radial
$C_{ur}$	12.400 N	Fatigue load limit, radial
$n_G$	8.700 1/min	Limiting speed
$n_{gr}$	5.100 1/min	Thermal speed rating
	0,72 kg	Weight

## Dimensions

	T7FB040	Comparative designation to ISO 10317 and ISO 355
$r_{1,2 \text{ min}}$	2 mm	Minimum chamfer dimension of inner ring back face
$r_{3,4 \text{ min}}$	1,5 mm	Minimum chamfer dimension of outer ring back face
a	30 mm	Distance between the apexes of the pressure cones
$d_1$	67,6 mm	Guidance rib diameter of inner ring

### Mounting dimensions

$d_{a \max}$	51 mm	Maximum diameter of shaft shoulder
$d_{b \min}$	49 mm	Minimum diameter of shaft shoulder
$D_{a \min}$	71 mm	Minimum diameter of housing shoulder
$D_{a \max}$	81 mm	Maximum diameter of housing shoulder
$D_{b \min}$	86 mm	Minimum diameter of housing shoulder
$C_{a \min}$	4 mm	Minimum axial space
$C_{b \min}$	8 mm	Minimum axial space
$r_{a \max}$	2 mm	Maximum fillet radius of shaft
$r_{b \max}$	1,5 mm	Maximum fillet radius of housing

### Calculation factors

e	0,83	Limiting value of $F_a/F_r$ for the applicability of diff. Values of factors X and Y
Y	0,73	Dynamic axial load factor
$Y_0$	0,4	Static axial load factor

### Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	120 °C	Operating temperature max.