

FAG

## ★ 30222-XL

Tapered roller bearing


Schaeffler ID:  
0932278250000

★ Preferred product

Tapered roller bearings 302, main dimensions to DIN ISO 355 / DIN 720, separable, adjusted or in pairs

X-life

## Technical information



## Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	120 °C	Operating temperature max.
	5,2 kg	Weight

## Main Dimensions &amp; Performance Data

d	110 mm	Bore diameter
D	200 mm	Outside diameter
B	38 mm	Width, inner ring
C	32 mm	Width, outer ring
T	41 mm	Width, total
$C_r$	375.000 N	Basic dynamic load rating, radial
$C_{0r}$	420.000 N	Basic static load rating, radial
$C_{ur}$	60.000 N	Fatigue load limit, radial
$n_G$	3.950 1/min	Limiting speed
$n_{gr}$	2.550 1/min	Thermal speed rating

## Dimensions

$r_{1,2 \min}$	3 mm	Minimum chamfer dimension of inner ring back face
$r_{3,4 \min}$	2,5 mm	Minimum chamfer dimension of outer ring back face
a	40 mm	Distance between the apices of the pressure cones
$d_1$	149,3 mm	Guidance rib diameter of inner ring

**Mounting dimensions**

$d_{a \max}$	129 mm	Maximum diameter of shaft shoulder
$d_{b \min}$	122 mm	Minimum diameter of shaft shoulder
$D_{a \min}$	174 mm	Minimum diameter of housing shoulder
$D_{a \max}$	188 mm	Maximum diameter of housing shoulder
$D_{b \min}$	187 mm	Minimum diameter of housing shoulder
$C_{a \min}$	6 mm	Minimum axial space
$C_{b \min}$	9 mm	Minimum axial space
$r_{a \max}$	3 mm	Maximum fillet radius of shaft
$r_{b \max}$	2,5 mm	Maximum fillet radius of housing

**Calculation factors**

	T3FB110	Comparative designation to ISO 10317 and ISO 355
$e$	0,42	Limiting value of $F_a/F_r$ for the applicability of diff. Values of factors X and Y
$Y$	1,43	Dynamic axial load factor
$Y_0$	0,79	Static axial load factor