




FAG

**KL68149-L68110**

Tapered roller bearing

Schaeffler ID:  
0192019580000Tapered roller bearing K-SERIES, single  
row

## Technical information

**Main Dimensions & Performance Data**

d	34,988 mm	Bore diameter
D	59,131 mm	Outside diameter
B	16,764 mm	Width, inner ring
C	11,938 mm	Width, outer ring
T	15,875 mm	Width, total
$C_r$	34.000 N	Basic dynamic load rating, radial
$C_{0r}$	44.500 N	Basic static load rating, radial
$C_{ur}$	5.100 N	Fatigue load limit, radial
$n_G$	12.400 1/min	Limiting speed
	0,002 kg	Weight

**Dimensions**

$r_{1,2 \text{ min}}$	3,6 mm	Minimum chamfer dimension of inner ring back face
$r_{3,4 \text{ min}}$	1,3 mm	Minimum chamfer dimension of outer ring back face
a	13 mm	Distance between the apexes of the pressure cones
$d_1$	48,8 mm	Guidance rib diameter of inner ring

**Mounting dimensions**

$d_{a \text{ max}}$	39 mm	Maximum diameter of shaft shoulder
$d_{b \text{ min}}$	45,5 mm	Minimum diameter of shaft shoulder
$D_{a \text{ min}}$	53 mm	Minimum diameter of housing shoulder
$D_{b \text{ min}}$	56 mm	Minimum diameter of housing shoulder
$C_{a \text{ min}}$	3 mm	Minimum axial space
$C_{b \text{ min}}$	4 mm	Minimum axial space
$r_{a \text{ max}}$	3,6 mm	Maximum fillet radius of shaft
$r_{b \text{ max}}$	1,3 mm	Maximum fillet radius of housing

**Calculation factors**

e	0,42	Limiting value of Fa/Fr for the applicability of diff. Values of factors X and Y
Y	1,44	Dynamic axial load factor
Y <sub>0</sub>	0,79	Static axial load factor

**Temperature range**

T <sub>min</sub>	-30 °C	Operating temperature min.
T <sub>max</sub>	120 °C	Operating temperature max.