

QL 3 DLI

Weidmüller Interface GmbH & Co. KG Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Product image







Similar to illustration

Numerous national and international approvals and qualifications in accordance with a variety of application standards make the W-series a universal connection solution, especially in harsh conditions. The screw connection has long been an established connection element to meet exacting demands in terms of reliability and functionality. And our W-Series is still setting standards.

General ordering data

Version	SAK Series, Cross-connection lug, Cross- connector, Number of poles: 3
Order No.	0297300000
Туре	QL 3 DLI
GTIN (EAN)	4008190034634
Qty.	50 pc(s).



QL 3 DLI

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Technical data

Dimensions	and	weights
Dillicitatoria	anu	Weignis

Dimensions and weights				
_				
Depth	0.8 mm	Depth (inches)	0.031 inch	
Height Width	4 mm 17.2 mm	Height (inches)	0.157 inch 0.677 inch	
Net weight	0.32 g	Width (inches)	0.677 Inch	
	0.32 g			
Temperatures				
Storage temperature	-25 °C55 °C			
Material data				
Material	Copper	Surface finish	tinned	
Colour	grey			
System specifications				
Version	Cross-connector			
Additional technical data	1			
Explosion-tested version	No	Installation advice	Direct mounting	
Type of fixing	when screwed in	Type of mounting	when screwed in	
Dimensions				
Pitch in mm (P)	6.1 mm			
	0.1 111111			
General				
Installation advice	Direct mounting	Number of poles	3	
Surface finish	tinned	Number of poles	3	
	uniod			
Rating data				
Rated current	20 A			
Classifications				
ETIM 6.0	EC000489	ETIM 7.0	EC000489	
ETIM 8.0	EC000489	ECLASS 9.0	27-14-11-40	
ECLASS 9.1	27-14-11-40	ECLASS 10.0	27-14-11-40 27-14-11-40	
ECLASS 11.0	27-14-11-40	ECLASS 12.0	27-14-11-40	
Approvals				
ROHS	Conform			
Downloads				
Engineering Data	CAD data – STEP			
User Documentation	StorageConditionsTerminalBlocks			
Osci Documentation	<u>Storage</u> Conditions term	III albiocks		