

SSCH 6X6X1000 CU/SN

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com



Of all the metals used, copper has the best electrical conductivity, which results in the highest short-circuit resistance. This makes the copper busbar the most widely used variant.

General ordering data

Version	Accessories, Busbar, Copper
Order No.	0571300000
Type	SSCH 6X6X1000 CU/SN
GTIN (EAN)	4008190015039
Qty.	1 m

Creation date March 3, 2023 11:42:30 AM CET

Catalogue status 18.02.2023 / We reserve the right to make technical changes.

SSCH 6X6X1000 CU/SN**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data**Dimensions and weights**

Depth	6 mm	Depth (inches)	0.236 inch
Height	1,000 mm	Height (inches)	39.37 inch
Width	6 mm	Width (inches)	0.236 inch
Net weight	320 g		

Material data

Material	Copper	Surface finish	tinned
Colour	silver		

Additional technical data

Installation advice	Direct mounting
---------------------	-----------------

General

Installation advice	Direct mounting	Surface finish	tinned
---------------------	-----------------	----------------	--------

Rating data

Rated current	140 A
---------------	-------

Classifications

ETIM 6.0	EC002848	ETIM 7.0	EC002848
ETIM 8.0	EC002848	ECLASS 9.0	27-14-11-92
ECLASS 9.1	27-14-11-92	ECLASS 10.0	27-14-11-92
ECLASS 11.0	27-14-11-92	ECLASS 12.0	27-14-11-92

Approvals

Approvals



ROHS	Conform
------	---------

Downloads

Approval/Certificate/Document of Conformity	EAC certificate
Engineering Data	CAD data – STEP
Engineering Data	WSCAD
User Documentation	StorageConditionsTerminalBlocks
Catalogues	Catalogues in PDF-format
Brochures	