

## IE-KSF-PKV14M-KLROB-7.5M

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)



Assembled IE cables

### General ordering data

Version	
Order No.	<a href="#">1103660075</a>
Type	IE-KSF-PKV 14M-KLROB-7.5M
GTIN (EAN)	4032248922376
Qty.	1 Stück

Erstellungs-Datum May 24, 2023 1:35:00 PM CEST

Katalogstand 12.05.2023 / Technische Änderungen vorbehalten

## IE-KSF-PKV14M-KLROB-7.5M

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 26  
 D-32758 Detmold  
 Germany

www.weidmueller.com

## Technische Daten

### Dimensions and weights

Net weight 980 g

### Temperatures

Operating temperature -40 °C...70 °C      Operating temperature, min. -40 °C  
 Operating temperature, max. 70 °C

### Electrical properties

Operating voltage 30 V

### General standards

Connector standard IEC 61076-3-119 CDV, IEC 61076-3-117 Var. 14

### Standards

Connector standard IEC 61076-3-119 CDV, IEC 61076-3-117 Var. 14

### Cable structure

Sheath diameter, max. 9.3 mm      Sheathing colour black (similar to RAL 9005)

### Electrical properties of cable

Operating voltage 30 V

### Mechanical and material properties of cable

Min. bending radius, once only 5 x cable diameter      Min. bending radius, repetitive 10 x cable diameter

### Classifications

ETIM 6.0	EC001579	ETIM 7.0	EC001579
ETIM 8.0	EC001579	ECLASS 9.0	27-06-24-90
ECLASS 9.1	27-06-24-00	ECLASS 10.0	27-06-05-01
ECLASS 11.0	27-06-05-01	ECLASS 12.0	27-06-05-01

### Environmental Product Compliance

REACH SVHC Lead 7439-92-1

### Approvals

ROHS Conform

## IE-KSF-PKV14M-KLROB-7.5M

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Technische Daten

### Downloads


User Documentation	<a href="#">MAN IE GUIDE DE</a> <a href="#">MAN IE GUIDE EN</a>
Catalogues	<a href="#">Catalogues in PDF-format</a>
Brochures	<a href="#">FL FIELDWIRING EN</a> <a href="#">PI PROFINET CABLING EN</a>

## IE-KSF-PKV14M-KLROB-7.5M

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Zeichnungen



STECKANLEITUNG  
14-POLIG

PAAR	BEZEICHNUNG
1	PAAR 1 (RED)
2	PAAR 2 (OR)
3	PAAR 3 (GR)
4	PAAR 4 (BL)
5	PAAR 5 (BR)
6	PAAR 6 (VIO)
7	PAAR 7 (GRN)
8	PAAR 8 (WHT)
9	PAAR 9 (BLK)
10	PAAR 10 (BRN)
11	PAAR 11 (GY)
12	PAAR 12 (PK)
13	PAAR 13 (LV)
14	PAAR 14 (SL)