

IE-KSF-PKV14M-KLROB-45M

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com



Assembled IE cables

General ordering data

Version	
Order No.	1103660450
Type	IE-KSF-PKV 14M-KLROB-45M
GTIN (EAN)	4032248922390
Qty.	1 Stück

Erstellungs-Datum May 24, 2023 1:36:30 PM CEST

Katalogstand 12.05.2023 / Technische Änderungen vorbehalten

IE-KSF-PKV14M-KLROB-45M

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany

www.weidmueller.com

Technische Daten

Dimensions and weights

Net weight 5,280 g

Temperatures

Operating temperature	-40 °C...70 °C	Operating temperature, min.	-40 °C
Operating temperature, max.	70 °C		

Electrical properties

Operating voltage 30 V

General standards

Connector standard IEC 61076-3-119 CDV, IEC 61076-3-117 Var. 14

Standards

Connector standard IEC 61076-3-119 CDV, IEC 61076-3-117 Var. 14

Cable structure

Sheath diameter, max.	9.3 mm	Sheathing colour	black (similar to RAL 9005)
-----------------------	--------	------------------	-----------------------------

Electrical properties of cable

Operating voltage 30 V

Mechanical and material properties of cable

Min. bending radius, once only	5 x cable diameter	Min. bending radius, repetitive	10 x cable diameter
--------------------------------	--------------------	---------------------------------	---------------------

Classifications

ETIM 6.0	EC001579	ETIM 7.0	EC001579
ETIM 8.0	EC001579	ECLASS 9.0	27-06-24-90
ECLASS 9.1	27-06-24-00	ECLASS 10.0	27-06-05-01
ECLASS 11.0	27-06-05-01	ECLASS 12.0	27-06-05-01

Environmental Product Compliance

REACH SVHC Lead 7439-92-1

Approvals

ROHS Conform

IE-KSF-PKV14M-KLROB-45M

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Technische Daten

Downloads


User Documentation	MAN IE GUIDE DE MAN IE GUIDE EN
Catalogues	Catalogues in PDF-format
Brochures	FL FIELDWIRING EN PI PROFINET CABLING EN

IE-KSF-PKV14M-KLROB-45M

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Zeichnungen



STECKANLEITUNG
TYPE 1000

PAAR	BEZEICHNUNG
1	PAAR 1 (S)
2	PAAR 2 (S)
3	PAAR 3 (S)
4	PAAR 4 (S)
5	PAAR 5 (S)
6	PAAR 6 (S)
7	PAAR 7 (S)
8	PAAR 8 (S)
9	PAAR 9 (S)
10	PAAR 10 (S)
11	PAAR 11 (S)
12	PAAR 12 (S)
13	PAAR 13 (S)
14	PAAR 14 (S)
15	PAAR 15 (S)
16	PAAR 16 (S)
17	PAAR 17 (S)
18	PAAR 18 (S)
19	PAAR 19 (S)
20	PAAR 20 (S)
21	PAAR 21 (S)
22	PAAR 22 (S)
23	PAAR 23 (S)
24	PAAR 24 (S)
25	PAAR 25 (S)
26	PAAR 26 (S)
27	PAAR 27 (S)
28	PAAR 28 (S)
29	PAAR 29 (S)
30	PAAR 30 (S)
31	PAAR 31 (S)
32	PAAR 32 (S)
33	PAAR 33 (S)
34	PAAR 34 (S)
35	PAAR 35 (S)
36	PAAR 36 (S)
37	PAAR 37 (S)
38	PAAR 38 (S)
39	PAAR 39 (S)
40	PAAR 40 (S)
41	PAAR 41 (S)
42	PAAR 42 (S)
43	PAAR 43 (S)
44	PAAR 44 (S)
45	PAAR 45 (S)
46	PAAR 46 (S)
47	PAAR 47 (S)
48	PAAR 48 (S)
49	PAAR 49 (S)
50	PAAR 50 (S)
51	PAAR 51 (S)
52	PAAR 52 (S)
53	PAAR 53 (S)
54	PAAR 54 (S)
55	PAAR 55 (S)
56	PAAR 56 (S)
57	PAAR 57 (S)
58	PAAR 58 (S)
59	PAAR 59 (S)
60	PAAR 60 (S)
61	PAAR 61 (S)
62	PAAR 62 (S)
63	PAAR 63 (S)
64	PAAR 64 (S)
65	PAAR 65 (S)
66	PAAR 66 (S)
67	PAAR 67 (S)
68	PAAR 68 (S)
69	PAAR 69 (S)
70	PAAR 70 (S)
71	PAAR 71 (S)
72	PAAR 72 (S)
73	PAAR 73 (S)
74	PAAR 74 (S)
75	PAAR 75 (S)
76	PAAR 76 (S)
77	PAAR 77 (S)
78	PAAR 78 (S)
79	PAAR 79 (S)
80	PAAR 80 (S)
81	PAAR 81 (S)
82	PAAR 82 (S)
83	PAAR 83 (S)
84	PAAR 84 (S)
85	PAAR 85 (S)
86	PAAR 86 (S)
87	PAAR 87 (S)
88	PAAR 88 (S)
89	PAAR 89 (S)
90	PAAR 90 (S)
91	PAAR 91 (S)
92	PAAR 92 (S)
93	PAAR 93 (S)
94	PAAR 94 (S)
95	PAAR 95 (S)
96	PAAR 96 (S)
97	PAAR 97 (S)
98	PAAR 98 (S)
99	PAAR 99 (S)
100	PAAR 100 (S)