

HDC HP 250 M CM3**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com



Crimps provide a electrical and mechanical connection between wire and contact that is both secure and reliable. The optimal crimp connection is gas-tight and corrosion-resistant.

General ordering data

Version	HDC insert, Pin, Crimp connection
Order No.	1415410000
Type	HDC HP 250 M CM3
GTIN (EAN)	4050118216370
Qty.	1 pc(s).

Creation date March 8, 2023 10:45:49 AM CET

Catalogue status 03.03.2023 / We reserve the right to make technical changes.

HDC HP 250 M CM3

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Net weight 41.21 g

Temperatures

Operating temperature, min. -40 °C Operating temperature, max. 125 °C

General data

Free from halogens false Material Copper alloy
Type Pin

Version

Material Copper alloy Type of connection Crimp connection

Classifications

ETIM 6.0	EC000796	ETIM 7.0	EC000796
ETIM 8.0	EC000796	ECLASS 9.0	27-44-02-04
ECLASS 9.1	27-44-02-04	ECLASS 10.0	27-44-02-04
ECLASS 11.0	27-44-02-04	ECLASS 12.0	27-44-02-04

Environmental Product Compliance

REACH SVHC Lead 7439-92-1
SCIP 6eabd5ae-2d6b-409e-8bdf-87c27ee10e40

Approvals

Approvals



ROHS Conform

Downloads

Engineering Data [CAD data – STEP](#)
Engineering Data [WSCAD](#)
Catalogues [Catalogues in PDF-format](#)
Brochures [FL FIELDWIRING EN](#)
[FL FIELDWIRING EN](#)