

DCDC 24V-120V 230W**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com



The compact DC/DC converter is designed for applications in automation technology, power supply and power plant technology, traffic system plus mechanical and plant engineering.

The DC/DC converter is characterised by its high efficiency and its above-average output data.

With status signalling and output voltage which can be shut off, it offers sensible functions for automation technology.

General ordering data

Order No.	1507190000
Type	DCDC 24V-120V 230W
GTIN (EAN)	4050118315615
Qty.	1 Stück

DCDC 24V-120V 230W

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany

www.weidmueller.com

Technische Daten

Dimensions and weights

Height	60 mm	Height (inches)	2.362 inch
Width	120 mm	Width (inches)	4.724 inch
Length	185 mm	Length (inches)	7.283 inch
Net weight	1,270 g		

Temperatures

Storage temperature	-40 °C...85 °C	Operating temperature	-40 °C...70 °C
Operating temperature, min.	-40 °C	Operating temperature, max.	70 °C
Humidity	5...95 %, no condensation		

Connection data (input)

Conductor cross-section, AWG/kcmil , max.	12	Conductor cross-section, AWG/kcmil , min.	26
Conductor cross-section, flexible , min.	0.5 mm ²	Conductor cross-section, rigid , max.	2.5 mm ²
Conductor cross-section, rigid , min.	0.5 mm ²	Reverse polarity protection	Yes
Wire connection cross section, flexible (input), max.	2.5 mm ²		

Connection data (output)

Conductor cross-section, AWG/kcmil , max.	12	Conductor cross-section, AWG/kcmil , min.	26
Conductor cross-section, flexible , max.	2.5 mm ²	Conductor cross-section, flexible , min.	0.5 mm ²
Conductor cross-section, rigid , max.	2.5 mm ²	Conductor cross-section, rigid , min.	0.5 mm ²
Number of terminals	1 terminal / 2-pole output ++/-	Reverse polarity protection	Yes

Connection data (signal)

Wire connection method	PUSH IN	Wire cross-section, solid , max.	2.5 mm ²
Wire cross-section, solid , min.	0.5 mm ²		

EMC / shock / vibration

Interference immunity test acc. to	EN 61000-4-11 (Dips), EN 61000-4-4 (burst), EN 61000-4-5 (surge), EN 61000-4-6 (conducted), EN61000-4-8 (Fields), EN 61000-4-2 (ESD), IEC 61000-4-3	Noise emission in accordance with EN55032	Class B
------------------------------------	---	---	---------

Electrical safety (applied standards)

Electrical machine equipment	Acc. to EN60204	For use with electronic equipment	Acc. to EN50178 / VDE0160
Safety extra-low voltage	SELV according to EN 60950, PELV according to EN 60204		

DCDC 24V-120V 230W

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany

www.weidmueller.com

Technische Daten

General data

Adjacent	Yes, no gap	Clip-in foot	metal
Current limiting	150% I _{out}	Degree of efficiency	93%
Housing version	Metal, corrosion resistant	Humidity	5...95 %, no condensation
Mounting position, installation notice	Horizontal on TS35 mounting rail. 50 mm of clearance at top & bottom for air circ. Can mount side by side with no space in between.	Short-circuit protection	Yes

Input

DC current consumption	Typ.: 11 A, Max.: 15.5 A	DC input voltage range	19,2 V DC ... 28,8 V DC
Input fuse (internal)	Yes	Input voltage, max.	28.8 V
Input voltage, min.	19.2 V	Inrush Current Limitation	< 10 A
Rated input voltage	24 V DC	Recommended back-up fuse	16 A / DI/II safety fuse, 16 A, char. B circuit breaker, 16 A, char. C, circuit breaker
Surge protection	Yes	Wire connection method	PUSH IN

Output

Output current	2 A	Output voltage type	DC
Output voltage, max.	144 V	Output voltage, min.	96 V
Output voltage, note	120 V @ > U _{IN} 27 V DC	Overload protection	Yes @ 3 A
Surge protection	Yes	Wire connection method	PUSH IN

Signalling

Remote on / off input	24 V DC signal	Remote on / off short-circuit-proof	yes
Status indicator	LED green (DC OK): input/output voltage = 16 V U _{INPUT} => 73 V U _{OUTPUT} , Red LED (fault) = 16 V U _{INPUT} = 0 V U _{OUTPUT}		

Classifications

ETIM 6.0	EC002540	ETIM 7.0	EC002540
ETIM 8.0	EC002540	ECLASS 9.0	27-04-07-01
ECLASS 9.1	27-04-07-01	ECLASS 10.0	27-04-07-01
ECLASS 11.0	27-04-07-01	ECLASS 12.0	27-04-07-01

Approvals

Approvals



ROHS

Conform