

**Q 4 WTL 6/4FF**

**Weidmüller Interfaces GmbH & Co. KG**

Postfach 3030

32760 Detmold

Tel. +49 5231 14-0

Fax. +49 5231 14-2083

info@weidmueller.com

www.weidmueller.com

**Product image**



Similar to illustration

**General ordering data**

|            |   |
|------------|---|
| Version    | W-Series, Cross-connector, Cross-connector,<br>Number of poles: 4 |
| Order No.  | <a href="#">1897130000</a>  |
| Type       | Q 4 WTL 6/4FF   |
| GTIN (EAN) | 4032248514106   |
| Qty.       | 100 pc(s).  |

## Q 4 WTL 6/4FF

Weidmüller Interfaces GmbH &amp; Co. KG

Postfach 3030

32760 Detmold

Tel. +49 5231 14-0

Fax. +49 5231 14-2083

info@weidmueller.com

www.weidmueller.com

## Technical data

## Dimensions and weights

|            |         |                 |            |
|------------|---------|-----------------|------------|
| Depth      | 6 mm    | Depth (inches)  | 0.236 inch |
| Height     | 41.8 mm | Height (inches) | 1.646 inch |
| Width      | 2 mm    | Width (inches)  | 0.079 inch |
| Net weight | 13.25 g |                 |            |

## Temperatures

|                     |                |
|---------------------|----------------|
| Storage temperature | -25 °C...55 °C |
|---------------------|----------------|

## Material data

|          |      |        |             |
|----------|------|--------|-------------|
| Material | CuSn | Colour | Silver grey |
|----------|------|--------|-------------|

## System specifications

|         |                 |
|---------|-----------------|
| Version | Cross-connector |
|---------|-----------------|

## Additional technical data

|                          |                 |                     |  |
|--------------------------|-----------------|---------------------|--|
| Explosion-tested version | No              | Installation advice | Feed-through (bushing),<br>Direct mounting |
| Type of fixing           | when screwed in | Type of mounting    | when screwed in                            |

## Dimensions

|                 |       |
|-----------------|-------|
| Pitch in mm (P) | 11 mm |
|-----------------|-------|

## General

|                     |  |                 |   |
|---------------------|--|-----------------|---|
| Installation advice | Feed-through (bushing),<br>Direct mounting | Number of poles | 4 |
|---------------------|--|-----------------|---|

## Rating data

|               |      |
|---------------|------|
| Rated current | 41 A |
|---------------|------|

## Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC000489    | ETIM 7.0    | EC000489    |
| ETIM 8.0    | EC000489    | ECLASS 9.0  | 27-14-11-40 |
| ECLASS 9.1  | 27-14-11-40 | ECLASS 10.0 | 27-14-11-40 |
| ECLASS 11.0 | 27-14-11-40 | ECLASS 12.0 | 27-14-11-40 |

## Approvals

|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

## Downloads

|                    |   |
|--------------------|---|
| Engineering Data   | <a href="#">CAD data – STEP</a>                 |
| User Documentation | <a href="#">StorageConditionsTerminalBlocks</a> |
| Catalogues         | <a href="#">Catalogues in PDF-format</a>        |
| Brochures          | <a href="#">CAT 1 TERM 16/17 EN</a>             |