

## SAIBW-M8-4P(TL)

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com







Individual cable lengths are often required nowadays. In order to meet these demands, Weidmüller offers a wide range of plug-in connectors for custom assembly. Male plugs and female sockets for customisable assembly for M8, M12, M16 and 7/8" connections which are highly robust and ideally suited to machine engineering, for instance. The M8 round plug-in connectors are particularly suited to applications where space is limited.

The solder connection provides high contact density on a small area. With this technology the stripped conductor is soldered to the contacts, producing good electrical conductivity.

#### **General ordering data**

Version	Field attachable connector, M8, Socket, angled
Order No.	<u>1920980000</u>
Туре	SAIBW-M8-4P(TL)
GTIN (EAN)	4032248562428
Qty.	1 pc(s).



# SAIBW-M8-4P(TL)

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

# **Technical data**

-			
Dım	ensions	and	weights

Net weight	9 a

#### **Temperatures**

Operating temperature, min.	-40 °C	Operating temperature, max.	85 °C	

### Technical data customisable plug-in connectors

Cable diameter	3.55 mm	Cable diameter, max.	5 mm
Cable diameter, min.	3.5 mm	Coding	none, A
Conductor cross-section, max.	0.25 mm <sup>2</sup>	Conductor cross-section, min.	0.25 mm <sup>2</sup>
Connection cross-section, max.	0.25 mm <sup>2</sup>	Connection cross-section, min.	0.25 mm <sup>2</sup>
Contact surface	Gold-plated	Housing main material	PA
Insulation strength	10 <sup>8</sup> Ω	Number of poles	4
Plugging cycles	≥ 100	Pollution severity	3
Protection degree	IP67	Rated current	4 A
Rated voltage	60 V	Rated voltage	60 V
Shield connection	No	Temperature range of housing	-40 +85 ° C
Threaded ring material	Diecast zinc	Type of connection	Solder connection

#### **Standards**

Connector standard	IEC 61076-2-104

#### Classifications

ETIM 6.0	EC002635	ETIM 7.0	EC002635
ETIM 8.0	EC002635	ECLASS 9.0	27-44-01-02
ECLASS 9.1	27-44-01-03	ECLASS 10.0	27-44-01-02
ECLASS 11.0	27-44-01-02	ECLASS 12.0	27-44-01-16

#### **Environmental Product Compliance**

REACH SVHC	Lead 7439-92-1
SCIP	ebf89fc8-a87f-4691-b87a-dfb9921774b4

#### **Approvals**

Approvals



ROHS	Conform
UL File Number Search	UL Website
Certificate no. (cULus)	E307231

#### **Downloads**

Engineering Data	CAD data – STEP	
Engineering Data	WSCAD	
Catalogues	Catalogues in PDF-format	
Brochures	FL FIELDWIRING EN	
	<u>FL FIELDWIRING EN</u>	