

MULTIMETER C 2608**Weidmüller Interfaces GmbH & Co. KG**

Postfach 3030

32760 Detmold

Tel. +49 5231 14-0

Fax. +49 5231 14-2083

info@weidmueller.com

www.weidmueller.com



Digital current clamp devices and attachments and adapters are used for measuring AC and DC currents. The significant advantage of these devices is that you can make a measurement without breaking the flow of current.

General ordering data

Version	Testing tools, Digital clamp-on measuring device
Order No.	9427370000
Type	MULTIMETER C 2608
GTIN (EAN)	4032248407019
Qty.	1 Stück

MULTIMETER C 2608

Weidmüller Interfaces GmbH & Co. KG

Postfach 3030

32760 Detmold

Tel. +49 5231 14-0

Fax. +49 5231 14-2083

info@weidmueller.com

www.weidmueller.com

Technische Daten

Dimensions and weights

Depth	108 mm	Depth (inches)	4.252 inch
Height	53 mm	Height (inches)	2.087 inch
Width	281 mm	Width (inches)	11.063 inch
Net weight	888.2 g		

Technical data

Description of article	Digital clamp-on measuring device
------------------------	-----------------------------------

Measuring and testing devices

AC voltage measuring range	0.66 - 750 V	Battery type	9V block battery
DC voltage measuring range	0.66 - 1000 V	Display	digital
Frequency measurement	Yes	Frequency range, max.	66 Hz
Frequency range, min.	1 MHz	Measured capacitance value, max.	6.6 mF
Measured capacitance value, min.	6.6 nF	Measured current value, max.	2,000 A
Measuring range category	CAT III	Opening width of current-measuring clamp-on attachment	57 mm
Resistance measuring range, max.	66 MΩ	Resistance measuring range, min.	660 Ω
Resolution of AC voltage	± 0.5%	Resolution of DC voltage	± 0.5%
Selection of measuring range	Manual	Tested and approved according to	EN/IEC 61010-1
Type of current	AC, DC	Working temperature, max.	50 °C
Working temperature, min.	0 °C		

Classifications

ETIM 6.0	EC000380	ETIM 7.0	EC000380
ETIM 8.0	EC000380	ECLASS 9.0	27-20-03-12
ECLASS 9.1	27-20-03-12	ECLASS 10.0	27-20-03-12
ECLASS 11.0	27-20-03-12	ECLASS 12.0	27-20-03-12

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
------------	----------------

Important note

Product information	Min/max function only applies for the DC range.
---------------------	---

Approvals

Approvals



ROHS	Conform
------	---------

MULTIMETER C 2608**Weidmüller Interfaces GmbH & Co. KG**

Postfach 3030

32760 Detmold

Tel. +49 5231 14-0

Fax. +49 5231 14-2083

info@weidmueller.comwww.weidmueller.com**Technische Daten****Downloads**

Product Change Notification

[Technical change DE](#)[Technical change EN](#)[20200312 Technische Änderung zu Strommesszange C 2606](#)[20200312 Technical change to Current clamp meter 2606](#)

User Documentation

[Operating instructions](#)

Catalogues

[Catalogues in PDF-format](#)

Brochures

MULTIMETER C 2608

Weidmüller Interfaces GmbH & Co. KG

Postfach 3030

32760 Detmold

Tel. +49 5231 14-0

Fax. +49 5231 14-2083

info@weidmueller.com

www.weidmueller.com

Zeichnungen

Example of use

