



Rods

Material: Stainless Steel, Aluminum, Brass, Pure Titanium Class 2



Rods		Material
O.D. Selectable	O.D. Configurable	
RDOF	-	EN 1.4305 Equiv.
RDOS	FRDOS	EN 1.4301 Equiv.
RDOH	-	EN 1.4401 Equiv.
RDOA	-	EN AW-2017 Equiv.
RDOK	-	EN AW-5056 Equiv.
RD52A	-	EN AW-5052 Equiv.
RDOG	-	EN CW614N Equiv. (Brass with Low Cadmium)
RDOT	-	Pure Titanium Class 2



or More	or Less	C
D3	D16	0.5
D17	D80	1.0

or More	or Less	Tolerance
10	30	±0.2
31	120	±0.3
121	400	±0.5
401	1000	±0.8

Rods (O.D. Selectable)

Part Number Type	D	L 1mm Increment
RDOF RDOS RDOH RDOA RDOK RD52A (D5~12, 15~20) RDOG RDOT (D3~6)	3	
	4	10~250
	5	
	6	
	8	10~500
	10	
	12	
	13	10~750
	15	
	16	10~900
18		
20	20~1000	
25		
30		
50	30~1000	
60		
80	30~200	



Ordering Example

Rods (O.D. Selectable)

Part Number - L
RDOA15 - 700

Rods (O.D. Configurable)

Part Number - D - L
FRDOS - D11 - L113

Rods (O.D. Configurable)

Part Number	D 1mm Increment	L 1mm Increment
FRDOS	6~10	10~500
	11~15	10~750
	16~17	10~900
	18~30	20~1000



Alterations

Part Number - L - (MC, WMC)
RDOF20 - 535 - MC8

O.D. Tolerance

Part Number D	RDOF RDOS	FRDOS RDOH RDOT	RDOA	RDOK RD52A RDOG
3				
4				
5				
6				
8				
10				
12	0	0	±0.1	
13	-0.1	-0.1		±0.1
15				
16				
18				
20				
25				
30				
50	0		±0.3	
60	-0.2			
80			±0.4	

Alterations	One End Tapped	Both Ends Tapped																															
Code	MC	WMC																															
Spec.	Adds a tap on one end. Ordering Code MC8 6 ≤ D ≤ 30 When L ≤ Mx2, the tap goes through.	Adds taps on both ends. Ordering Code WMC12 6 ≤ D ≤ 30 When L ≤ Mx4, the tap goes through.																															
	<table border="1"> <thead> <tr><th>D</th><th>MC (Selection Range)</th></tr> </thead> <tbody> <tr><td>6, 7</td><td>3</td></tr> <tr><td>8, 9</td><td>3, 4</td></tr> <tr><td>10, 11</td><td>3, 4, 5</td></tr> <tr><td>12~14</td><td>3, 4, 5, 6</td></tr> <tr><td>15~19</td><td>3, 4, 5, 6, 8</td></tr> <tr><td>20~24</td><td>3, 4, 5, 6, 8, 10, 12</td></tr> <tr><td>25~30</td><td>3, 4, 5, 6, 8, 10, 12, 16</td></tr> </tbody> </table> When L ≤ Mx4, the pilot hole for tapping may go through.	D	MC (Selection Range)	6, 7	3	8, 9	3, 4	10, 11	3, 4, 5	12~14	3, 4, 5, 6	15~19	3, 4, 5, 6, 8	20~24	3, 4, 5, 6, 8, 10, 12	25~30	3, 4, 5, 6, 8, 10, 12, 16	<table border="1"> <thead> <tr><th>D</th><th>WMC (Selection Range)</th></tr> </thead> <tbody> <tr><td>6, 7</td><td>3</td></tr> <tr><td>8, 9</td><td>3, 4</td></tr> <tr><td>10, 11</td><td>3, 4, 5</td></tr> <tr><td>12~14</td><td>3, 4, 5, 6</td></tr> <tr><td>15~19</td><td>3, 4, 5, 6, 8</td></tr> <tr><td>20~24</td><td>3, 4, 5, 6, 8, 10, 12</td></tr> <tr><td>25~30</td><td>3, 4, 5, 6, 8, 10, 12, 16</td></tr> </tbody> </table>	D	WMC (Selection Range)	6, 7	3	8, 9	3, 4	10, 11	3, 4, 5	12~14	3, 4, 5, 6	15~19	3, 4, 5, 6, 8	20~24	3, 4, 5, 6, 8, 10, 12	25~30
D	MC (Selection Range)																																
6, 7	3																																
8, 9	3, 4																																
10, 11	3, 4, 5																																
12~14	3, 4, 5, 6																																
15~19	3, 4, 5, 6, 8																																
20~24	3, 4, 5, 6, 8, 10, 12																																
25~30	3, 4, 5, 6, 8, 10, 12, 16																																
D	WMC (Selection Range)																																
6, 7	3																																
8, 9	3, 4																																
10, 11	3, 4, 5																																
12~14	3, 4, 5, 6																																
15~19	3, 4, 5, 6, 8																																
20~24	3, 4, 5, 6, 8, 10, 12																																
25~30	3, 4, 5, 6, 8, 10, 12, 16																																

Rods (O.D. Selectable)

Part Number Type	D	Unit Price					
		Min. L - 100	101-200	201-400	401-600	601-800	801-1000
RDOF (EN 1.4305 Equiv.)	3						
	4						
	5						
	6						
	8						
	10						
	12						
	13						
	15						
	16						
	18						
	20						
	25						
	30						
	50						
60							
80							
RDOS (EN 1.4301 Equiv.)	3						
	4						
	5						
	6						
	8						
	10						
	12						
	13						
	15						
	16						
	18						
	20						
	25						
	30						
	50						
60							
80							
RDOH (EN 1.4401 Equiv.)	3						
	4						
	5						
	6						
	8						
	10						
	12						
	13						
	15						
	16						
	18						
	20						
	25						
	30						
	RDOA (EN AW-2017 Equiv.)	3					
4							
5							
6							
8							
10							
12							
13							
15							
16							
18							
20							
25							
30							

For maximum L dimension in each D dimension, refer to the specification table shown on the left-hand page.

Part Number Type	D	Unit Price					
		Min. L - 100	101-200	201-400	401-600	601-800	801-1000
RDOK (EN AW-5056 Equiv.)	3						
	4						
	5						
	6						
	8						
	10						
	12						
	13						
	15						
	16						
RD52A (EN AW-5052 Equiv.)	5						
	6						
	8						
	10						
	12						
	15						
RDOG (EN CW614N Equiv.)	16						
	18						
	20						
	3						
	4						
	5						
	6						
	8						
	10						
	12						
RDOT (Pure Titanium Class 2)	13						
	15						
	16						
	18						
	20						
	25						

Rods (O.D. Configurable)

Part Number	D 1mm Increment	Unit Price					
		Min. L - 100	101-200	201-400	401-600	601-800	801-1000
FRDOS (EN 1.4301 Equiv.)	6~10						
	11~15						
	16~19						
	20~24						
	25~27						
	28~30						