Extruded Brackets - For 4 Slots / Thin Brackets

For 8-45 Series (Slot Width 10mm) Aluminum Extrusions







Plate Brackets / Angled Brackets

For 8-45 Series (Slot Width 10mm) Aluminum Extrusions







	Part Number	Mass	Applic	able Screw, T Nut			Allowable	Unit Price	Volume Discount Rate		Part Nu
		(g)	Screw	Quantity	T Nut	Quantity	Load (N)	1~99 pc(s).	100~200		Part Nu
Ì	HBLUQ8-45	846	CBM8-25	8	HNTT8-8	8	7056				HBLPG
í	Ordering Pa	ert Nice	nhor								HBLPG
н	Uraerina i u		ibci								




Alterations	Code	Spec.	Applicable Bracket
Mounting Hole		Adds taps on a bracket for cover mounting. (M5 on Both Sides)	HBLUQ8-45
Alteration for Cover			HBLPQ8-200

Alterations	Code Spec.			
Applicable Screws and Nuts Set		Applicable screws and nuts for fixing the brackets on extrusions come in a set. (Adds to the bracket price) (When specifying other than HBLU08-45, check for the applicable screws and nuts.	(Ex.) When HBLU08-45 is specified: Code Screw Nut SET CBM8-25 HNTT8-8 SST SCB8-25 HNTT8-8 SEU CBM8-25 HNTU8-8 SSU SCB8-25 SHNTU8-8 SEP CBM8-25 HNTP8-8 SSP SCB8-25 SHNTP8-8	Applicable Bracket HBLUQ8-45 HBLPQ8-200
			SEC HCBST8-29 HNTT8-8	


Included Screw is not RoHS compliant when -SET, -SEU or -SEP are specified.

Features: The brackets do not protrude from extrusion widths when used to cross connect extrusions.



EN AC-51400-T5 Equiv.

HBLSD8-45



Space-saving design compared to Tabbed Reversal Brackets.							
Thin Brackets HBLSD8-45 4-09 22.5 14 10 51							

Part Number	Mass	Applicab	le S	Screw, T N	lut	Allowable	Unit Price	Volume Discount Rati
Part Number	(g)	Screw	Quantity	T Nut	Quantity	(N)	1~99 pc(s).	100~200
HBLSS8-45	52	CBM8-25	2	HNTT8-8	2	1666		
HBLSD8-45	175	CDIVIO-23	4	ПИ110-0	4	2352		




Ordering Part Number




Alterations	Code	Spec.	Applicable Bracket
Applicable Screws and Nuts Set	SET SST (Stainless Steel) SEU (Pre-Assembly Insertion Spring Nuts) SSU (Pre-Assembly Insertion Spring Nuts Stainless Steel) SEP (Post-Assembly Insertion Spring Nuts) SSP (Post-Assembly Insertion Spring Nuts Stainless Steel)	Applicable screws and nuts for fixing the brackets on extrusions come in a set. (Adds to the bracket price) <when is="" set="" specified=""> Screw: CBM8-25, Nut: HNTT8-8 <when is="" set="" specified=""> Screw: SCB8-25, Nut: HNTT8N8-8 <when is="" seu="" specified=""> Screw: CBM8-25, Nut: HNTU8-8 <when is="" seu="" specified=""> Screw: SCB8-25, Nut: SHNTU8-8 <when is="" sep="" specified=""> Screw: CBM8-25, Nut: HNTP8-8 <when is="" sep="" specified=""> Screw: CBM8-25, Nut: HNTP8-8 <when is="" sep="" specified=""> Screw: SCB8-25, Nut: SHNTP8-8</when></when></when></when></when></when></when>	HBLSS8-45


Included Screw is not RoHS compliant when -SET, -SEU or -SEP are specified.











BL451S8	HBL1351S8
2-09 12 12 04.2 30 9 70 80	2-M8 Counterbore (West specifying allocation 26)

	Part Number	Mass	Applica	ble S	crew, T I	Nut	Allowable Load	Unit Price	Volume Discount Rate
	Part Number	(g)	Screw	Quantity	T Nut	Quantity	(N)	1~99 pc(s).	100~200
	HBL45TS8	88	CBM8-20	2	HNTT8-8	2	2058		
	HBI 135TS8	103							

Part Number - (C, SET, SST, SEU, SSU, SEP, SSP, Z8)

Applicable Bracket

Spec.

Adds taps on a bracket for cover

(M5 on Both Sides, Depth 15mm)

(Mounting Screw HCBM on P.754)

mounting



Alterations Code


Mounting Hole

Alteration for

Cover

HBL135TS8





Alterations	Code	Spec.	Applicable Bracket	
Applicable Screws	SET SST (Stainless Steel) SEU (Pre-Assembly Insertion) SSU (Pre-Assembly Insertion) (Pre-Assembly Insertion)	Applicable screws and nuts for fixing the brackets on extrusions come in a set. (Adds to the bracket price) Ex.) <when is="" set="" specified=""> Screw: CBM8-25, Nut: HNTT8-8, <when is="" set="" specified=""> Screw: SCB8-25, Nut: HNTTSN8-8, <when is="" set="" specified=""></when></when></when>	HBL45TS8	
and Nuts Set	Spring Nuts Stainless Steel SEP (Post-Assembly Insertion Spring Nuts SSP (Post-Assembly Insertion Spring Nuts Stainless Steel	Screw: CBM8-25, Nut: HNTU8-8, <when is="" specified="" ssu=""></when>	HBL135TS8	
Counterbored Holes on 135 Degree Bracket	Z8	135 Degree Bracket 2 Counterbore holes for HBL135TS8 (Applicable Screws: M8) Applicable Screws: M8) Not available in combination with Applicable Screws and Nuts	HBL135TS8	

