


A Dimension Configurable Plates - EN 1.0038 Equiv. 6F Equiv. (Economy)




Features of Precision Cut Plates: Economical and short delivery time

Base material is milled on top, bottom and side surfaces for cut to precise lengths by 1mm increment for shipments. Economical and short delivery time.



SS400-CUT



Reference Length	~600mm	600.1~1200mm
Length (A)	±0.1	±0.2
Width (B)		±0.1
Thickness (T)		±0.1

M Material: EN 1.0038 Equiv.

Type	A: 0.1mm Increment	B	T																														
				5	6	8	9	10	11	12	13	14	15	16	18	19	20	22	25	28	30	32											
SS400-CUT	15 - 50	15	15																														
	50.1 - 100																																
	100.1 - 250																																
	250.1 - 400																																
	400.1 - 600																																
	600.1 - 1000																																
	1000.1 - 1200																																
	16 - 50			16	16																												
	50.1 - 100																																
	100.1 - 250																																
250.1 - 400																																	
400.1 - 600																																	
600.1 - 1000																																	
1000.1 - 1200																																	
20 - 50	20	20																															
50.1 - 100																																	
100.1 - 250																																	
250.1 - 400																																	
400.1 - 600																																	
600.1 - 1000																																	
1000.1 - 1200																																	
22 - 50	22	22																															
50.1 - 100																																	
100.1 - 250																																	
250.1 - 400																																	
400.1 - 600																																	
600.1 - 1000																																	
1000.1 - 1200																																	
25 - 50	25	25																															
50.1 - 100																																	
100.1 - 250																																	
250.1 - 400																																	
400.1 - 600																																	
600.1 - 1000																																	
1000.1 - 1200																																	
30 - 50	30	30																															
50.1 - 100																																	
100.1 - 250																																	
250.1 - 400																																	
400.1 - 600																																	
600.1 - 1000																																	
1000.1 - 1200																																	
32 - 50	32	32																															
50.1 - 100																																	
100.1 - 250																																	
250.1 - 400																																	
400.1 - 600																																	
600.1 - 1000																																	
1000.1 - 1200																																	
35 - 50	35	35																															
50.1 - 100																																	
100.1 - 250																																	
250.1 - 400																																	
400.1 - 600																																	
600.1 - 1000																																	
1000.1 - 1200																																	
38 - 50	38	38																															
50.1 - 100																																	
100.1 - 250																																	
250.1 - 400																																	
400.1 - 600																																	
600.1 - 1000																																	
1000.1 - 1200																																	
40 - 50	40	40																															
50.1 - 100																																	
100.1 - 250																																	
250.1 - 400																																	
400.1 - 600																																	
600.1 - 1000																																	
1000.1 - 1200																																	
45 - 50	45	45																															
50.1 - 100																																	
100.1 - 250																																	
250.1 - 400																																	
400.1 - 600																																	
600.1 - 1000																																	
1000.1 - 1200																																	
50 - 100	50	50																															
100.1 - 250																																	
250.1 - 400																																	
400.1 - 600																																	
600.1 - 1000																																	
1000.1 - 1200																																	
55 - 100	55	55																															
100.1 - 250																																	
250.1 - 400																																	
400.1 - 600																																	
600.1 - 1000																																	
1000.1 - 1200																																	
60 - 100	60	60																															
100.1 - 250																																	
250.1 - 400																																	
400.1 - 600																																	
600.1 - 1000																																	
1000.1 - 1200																																	
65 - 100	65	65																															
100.1 - 250																																	
250.1 - 400																																	
400.1 - 600																																	
600.1 - 1000																																	
1000.1 - 1200																																	



Ordering Example Part Number - **A - B - T**
SS400-CUT - 100 - 100 - 10

Precision Standards (Max. Value)

Item	Condition	Standard Value
Width Parallelism	Length Min. ~ 200mm	0.03
	Length 200.1 ~ 500mm	0.05
	Length 500.1 ~ Max.	0.1
Thickness Parallelism		0.05
Flatness	T5-15	0.05
	T16-25	0.04
	T26-32	0.03
Perpendicularity (Each Plane)	To Length 100mm and Width 100mm	0.05
Circumference Chamfering	To be free of burrs. Chamfering may be about C0.1.	

Type	A: 0.1mm Increment	B	T																														
				5	6	8	9	10	11	12	13	14	15	16	18	19	20	22	25	28	30	32											
SS400-CUT	70 - 100	70	70																														
	100.1 - 250																																
	250.1 - 400																																
	400.1 - 600																																
	600.1 - 1000																																
	1000.1 - 1200																																
	75 - 100			75	75																												
	100.1 - 250																																
	250.1 - 400																																
	400.1 - 600																																
600.1 - 1000																																	
1000.1 - 1200																																	
80 - 100	80	80																															
100.1 - 250																																	
250.1 - 400																																	
400.1 - 600																																	
600.1 - 1000																																	
1000.1 - 1200																																	
85 - 100	85	85																															
100.1 - 250																																	
250.1 - 400																																	
400.1 - 600																																	
600.1 - 1000																																	
1000.1 - 1200																																	
90 - 100	90	90																															
100.1 - 250																																	
250.1 - 400																																	
400.1 - 600																																	
600.1 - 1000																																	
1000.1 - 1200																																	
95 - 100	95	95																															
100.1 - 250																																	
250.1 - 400																																	
400.1 - 600																																	
600.1 - 1000																																	
1000.1 - 1200																																	
100 - 250	100	100																															
250.1 - 400																																	
400.1 - 600																																	
600.1 - 1000																																	
1000.1 - 1200																																	
105 - 250	105	105																															
250.1 - 400																																	
400.1 - 600																																	
600.1 - 1000																																	
1000.1 - 1200																																	
110 - 250	110	110																															
250.1 - 400																																	
400.1 - 600																																	
600.1 - 1000																																	
1000.1 - 1200																																	
115 - 250	115	115																															
250.1 - 400																																	
400.1 - 600																																	
600.1 - 1000																																	
1000.1 - 1200																																	
120 - 250	120	120																															
250.1 - 400																																	
400.1 - 600																																	
600.1 - 1000																																	
1000.1 - 1200																																	
125 - 250	125	125																															
250.1 - 400																																	
400.1 - 600																																	
600.1 - 1000																																	
1000.1 - 1200																																	
130 - 250	130	130																															
250.1 - 400																																	
400.1 - 600																																	
600.1 - 1000																																	
1000.1 - 1200																																	
140 - 250	140	140																															
250.1 - 400																																	
400.1 - 600																																	
600.1 - 1000																																	
1000.1 - 1200																																	
150 - 250	150	150																															
250.1 - 400																																	
400.1 - 600																																	
600.1 - 1000																																	
1000.1 - 1200																																	
180 - 250	180	180																															
250.1 - 400																																	
400.1 - 600																																	
600.1 - 1000																																	
1000.1 - 1200																																	
200 - 250	200	200																															
250.1 - 400																																	
400.1 - 600																																	
600.1 - 1000																																	
1000.1 - 1200																																	