

ALPHA WIRE
CUSTOMER PRODUCT SPECIFICATION

Part Number: B951023
Page 1 of 2 Pages

Issue: 2
Issue Date: 1/4/2013
Effective Date: 1/18/2013

A. Construction

					<u>Diameters (mm)</u>
1)	Component 1	2 X 1 COND			
a)	Conductor	28 (7/36) AWG TC			0.38
b)	Insulation	0.25 Wall, Nom. PVC, Semi Rigid			0.89
(1)	Color Code	Alpha Wire Color Code E			
			Cond	Color	
			1	BLACK	
			2	BROWN	
2)	Cable Assembly	2 Components Cabled			
a)	Twists:	52.5 Twists/meter (min)			
b)	Core Wrap	Clear Mylar Tape, 25% Overlap, Min.			
3)	Shield	TC BRAID Shield, 85% Coverage, Min.			
a)	Drain Wire	28 (7/36) AWG TC			
4)	Jacket	0.81 Wall, Nom., PVC			4.04 (4.28 Max.)
a)	Color(s)	GREY			
b)	Ripcord	1 End 810 Denier Nylon			
c)	Print	ALPHA WIRE-* P/N B951023 0.09MM2 (28AWG) (UL) TYPE CM 105C OR AWM 2464 VW-1 --- LLXXXXXX CSA 105C TYPE CMG FT4 ROHS (SEQ METERS)			
		* = Factory Code			

[Note: Product may have c(UL) or CSA markings depending upon plant of manufacture.]

B. Applicable Specifications

1)	UL	AWM/STYLE 10002	105°C / 300 V _{RMS}
	a)	Component 1	80°C / 300 V _{RMS}
	b)	Overall	CM
		CM	105°C
2)	VW-1	CMG	105°C
3)	CSA International	FT4	
4)	IEC	EN 60332-1 Flame Behavior	
		EN 60332-2 Flame Behavior	
4)	CE:	EU Low Voltage Directive 2006/95/EC	

C. Environmental Compliance

1)	CE:	EU Directive 2011/65/EU(RoHS2): This product complies with European Directive 2011/65/EU (RoHS Directive) of the European Parliament and of the Council of 8 June 2011. No Exemptions are required for RoHS Compliance on this item. Consult Alpha Wire's web site for RoHS C of C .
2)	REACH Regulation (EC 1907/2006):	This product does not contain Substances of Very High Concern (SVHC) listed on the European Union's REACH candidate list in excess of 0.1% mass of the item. For up-to-date information, please see Alpha's REACH SVHC Declaration .

D. Physical & Mechanical Properties

1)	Temperature Range	-30 to 105°C
2)	Bend Radius	10X Cable Diameter
3)	Pull Tension	6.1 Lbs, Maximum
4)	Sunlight Resistance	Yes

E. Electrical Properties

1)	Voltage Rating	300 V _{RMS}
2)	Capacitance	88.56 pf/m @1 kHz, Nominal Conductor to Conductor
3)	Ground Capacitance	160.72 pf/m @1 kHz, Nominal
4)	Characteristic Impedance	70 Ω

Although Alpha Wire Company ("Alpha") makes every reasonable effort to ensure their accuracy at the time of publication, information and specifications described herein are subject to errors or omissions and to changes without notice, and the listing of such information and specifications does not ensure product availability.

Alpha provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Alpha be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary) whatsoever, even if Alpha has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

ALPHA WIRE
CUSTOMER PRODUCT SPECIFICATION

Part Number: B951023
Page 2 of 2 Pages

Issue: 2
Issue Date: 1/4/2013
Effective Date: 1/18/2013

5) Inductance 0.7216 μ H/m, Nominal
6) Conductor DCR 216.48 Ω /Km @20°C, Nominal
7) OA Shield DCR 34.768 Ω /Km @20°C, Nominal

F. Other

1) Packaging Flange x Traverse x Barrel (inches)
a) 3280 FT 16 x 11 x 8 Continuous length
b) 1640 FT 12 x 10 x 5 Continuous length
c) 328 FT 6.5 x 6 x 1.9 Continuous length
d) 164 FT 6.5 x 4 x 2.5 Continuous length
[Spool dimensions may vary slightly]

Although Alpha Wire Company ("Alpha") makes every reasonable effort to ensure their accuracy at the time of publication, information and specifications described herein are subject to errors or omissions and to changes without notice, and the listing of such information and specifications does not ensure product availability.

Alpha provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Alpha be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary) whatsoever, even if Alpha has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.