

ALPHA WIRE

CUSTOMER PRODUCT SPECIFICATION

Part Number: B961023	Issue: 2
Page 1 of 2 Pages	Issue Date: 1/4/2013
	Effective Date: 1/18/2013

A. Construction

1)	Component 1	2 X 1 PAIR	
	a) Conductor	28 (7/36) AWG TC	0.38
	b) Insulation	0.25 Wall, Nom. PVC, Semi Rigid	0.89
	(1) Color Code	Alpha Wire Color Code B	

Pair	Color	Pair	Color	Pair	Color
1	WHITE-BLACK	2	WHITE-BROWN		

c)	Pair	2/Cond Cabled Together	
	(1) Twists:	39.4 Twists/meter (min)	
2)	Cable Assembly	2 Components Cabled	
a)	Twists:	31.5 Twists/meter (min)	
b)	Core Wrap	Clear Mylar Tape, 25% Overlap, Min.	
3)	Shield	TC BRAID Shield, 85% Coverage, Min.	
a)	Drain Wire	28 (7/36) AWG TC	
4)	Jacket	0.81 Wall, Nom., PVC	5.18 (5.50 Max.)
a)	Color(s)	GREY	
b)	Ripcord	1 End 810 Denier Nylon	
c)	Print	ALPHA WIRE-* P/N B961023	
		0.09MM2 (28AWG) (UL) TYPE CM 105C OR AWM 2464	

[Note: Product may have c(UL) or CSA markings depending upon plant of manufacture.]

B. Applicable Specifications

1) UL	Component 1	AWM/STYLE 10002	105°C / 300 V _{RMS}
	Overall	AWM/STYLE 2464	80°C / 300 V _{RMS}
		CM	105°C
		VW-1	
2) CSA International		CMG	105°C
		FT4	
3) IEC		EN 60332-1 Flame Behavior	
		EN 60332-2 Flame Behavior	
4) CE:		EU Low Voltage Directive 2006/95/EC	

c. Environmental Compliance

1) CE: EU Directive 2011/65/EU(RoHS2):
This product complies with European Directive 2011/65/EU (RoHS Directive) of the European Parliament and of the Council of 8 June 2011. No Exemptions are required for RoHS Compliance on this item. Consult Alpha Wire's web site for [RoHS C of C](#).

2) REACH Regulation (EC 1907/2006):
This product does not contain Substances of Very High Concern (SVHC) listed on the European Union's REACH candidate list in excess of 0.1% mass of the item. For up-to-date information, please see [Alpha's REACH SVHC Declaration](#).

D. Physical & Mechanical Properties

Physical & Mechanical Properties	
1) Temperature Range	-30 to 105°C
2) Bend Radius	10X Cable Diameter
3) Pull Tension	10.8 Lbs, Maximum
4) Sunlight Resistance	Yes

4) Sunlight Resistance

Electrical Properties		(For Engineering purposes only)
1)	Voltage Rating	300 V _{RMS}
2)	Mutual Capacitance	71.504 pF/m @ 1 kHz, Nominal

Although Alpha Wire Company ("Alpha") makes every reasonable effort to ensure their accuracy at the time of publication, information and specifications described herein are subject to errors or omissions and to changes without notice, and the listing of such information and specifications does not ensure product availability.

Alpha provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Alpha be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary) whatsoever, even if Alpha has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

ALPHA WIRE
CUSTOMER PRODUCT SPECIFICATION

Part Number: B961023
Page 2 of 2 Pages

Issue: 2
Issue Date: 1/4/2013
Effective Date: 1/18/2013

3) Ground Capacitance	127.92 pf/m @1 kHz, Nominal
4) Characteristic Impedance	82 Ω
5) Inductance	0.7216 μH/m, Nominal
6) Conductor DCR	219.76 Ω/Km @20°C, Nominal
7) OA Shield DCR	15.088 Ω/Km @20°C, Nominal

F. Other

1) Packaging	Flange x Traverse x Barrel (inches)
a) 3280 FT	18 x 12 x 8 Continuous length
b) 1640 FT	12 x 12 x 3.5 Continuous length
c) 328 FT	12 x 4.5 x 3.5 Continuous length
d) 164 FT	12 x 4.5 x 3.5 Continuous length

[Spool dimensions may vary slightly]

Although Alpha Wire Company ("Alpha") makes every reasonable effort to ensure their accuracy at the time of publication, information and specifications described herein are subject to errors or omissions and to changes without notice, and the listing of such information and specifications does not ensure product availability.

Alpha provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Alpha be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary) whatsoever, even if Alpha has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.