

Coaxial Cable Connector 11_N-50-3-5/133_N

Description

Straight cable plug

Interface standards

IEC 61169-16_MIL-STD-348A/304_CECC 22210



Technical Data

Electrical Data

| | |
|--------------------------|--------|
| Impedance | 50 Ω |
| Interface frequency max. | 11 GHz |

Mechanical Data

| | |
|----------------|-----------|
| Centre contact | soldered |
| Outer contact | clamped |
| Weight | 0.0365 kg |

Environmental Data

| | |
|-----------------------|------------------|
| Operating temperature | -65 °C to 165 °C |
| 2011/65/EU (RoHS) | compliant |

Material Data

| Piece Parts | Material | Surface Plating |
|----------------|-----------------------|-----------------------------------|
| Centre contact | Brass | Gold Plating (Nickel underplated) |
| Outer contact | Brass | SUCOPLADE (R) Plating |
| Body | Brass | SUCOPLADE (R) Plating |
| Insulator | PFA / PTFE | |
| Coupling nut | Brass | SUCOPLADE (R) Plating |
| Gasket | VMQ (Silicone rubber) | |

Related Documents

| | |
|----------------------|----------------|
| Outline drawing | DOU-00008106 |
| Catalogue drawing | DOU-00006125 |
| Assembly instruction | DOC-0000177464 |

Ordering Information

| | |
|----------------------|--------------------|
| Bulk 100 pcs package | 11_N-50-3-5/133_NH |
| Single package | 11_N-50-3-5/133_NE |

Additional Information

| | |
|-----------------|--|
| Suitable cables | RADOX_RF_400, ENVIROFLEX_142, RG_400/_U, RG_223/_U, RG_142_B/U |
|-----------------|--|