

Relay connectors - ST-REL4-KG230/21-21/AU - 2826431

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Relay connector, fitted with miniature switching relay, contacts (AgNi+Au): Small to large loads, 2 PDT, 230 V AC/DC input voltage, with light indicator, can be plugged into basic terminal blocks

The illustration shows version ST-REL 4-KG 24/21-21/AU

Key commercial data

package_quantity	10
GTIN	4017918077914

Technical data

Dimensions

Width	27 mm
Height	33 mm
Depth	66.5 mm

Ambient conditions

Ambient temperature (operation)	-20 °C ... 50 °C
Ambient temperature (storage/transport)	-20 °C ... 70 °C

Coil side

Nominal input voltage U_N	230 V AC/DC
Input voltage range in reference to U_N	0.8 ... 1.06
Nominal input current at U_{IN}	5 mA
Typical response time	6 ms (with DC)
Typical release time	7 ms (with DC)
Operating voltage display	Yes
Protective circuit	Bridge rectifier Bridge rectifier
Protective circuit	Surge protection Varistor

Contact side

Contact type	Single contact, 2-PDT
Contact material	Hard gold plated AgNi
Maximum switching voltage	30 V AC/DC
Maximum switching voltage	250 V AC/DC
Maximum inrush current	50 mA
Limiting continuous current	50 mA

Relay connectors - ST-REL4-KG230/21-21/AU - 2826431

Technical data

Contact side

Interrupting rating (ohmic load) max.	1.2 W (at 24 V DC)
Interrupting rating (ohmic load) max.	5 VA (for 24 V AC)
Note	the following values are applicable if a gold layer is destroyed
Maximum switching voltage	250 V AC/DC
Limiting continuous current	3 A
Maximum inrush current	5 A
Interrupting rating (ohmic load) max.	70 W (at 24 V DC)
Interrupting rating (ohmic load) max.	85 W (at 48 V DC)
Interrupting rating (ohmic load) max.	60 W (at 60 V DC)
Interrupting rating (ohmic load) max.	40 W (at 110 V DC)
Interrupting rating (ohmic load) max.	55 W (at 220 V DC)
Interrupting rating (ohmic load) max.	750 VA (for 250 V AC)

General

Test voltage relay winding/relay contact	2.5 kV AC (50 Hz, 1 min.)
Test voltage PDT/PDT	1 kV AC (50 Hz, 1 min.)
Operating mode	100% operating factor
Mechanical service life	Approx. 2×10^7 cycles
Standards/regulations	DIN VDE 0110b, Gr. C for 250 V DC
Standards/regulations	IEC 60255/DIN VDE 0435 (in relevant parts)
Standards/regulations	DIN EN 50178/DIN VDE 0160 (in relevant parts)
Standards/regulations	EN 60730/DIN VDE 0631
Standards/regulations	DIN VDE 0160 (in relevant parts)

classifications

eCl@ss

eCl@ss 4.0	27371104
eCl@ss 4.1	27371104
eCl@ss 5.0	27371001
eCl@ss 5.1	27371001
eCl@ss 6.0	27371001
eCl@ss 7.0	27371001
eCl@ss 8.0	27371001

ETIM

ETIM 2.0	EC000196
ETIM 3.0	EC000196
ETIM 4.0	EC000196
ETIM 5.0	EC000196

UNSPSC

UNSPSC 6.01	30211916
-------------	----------

Relay connectors - ST-REL4-KG230/21-21/AU - 2826431

classifications


UNSPSC

UNSPSC 7.0901	39121515
UNSPSC 11	39121515
UNSPSC 12.01	39121515
UNSPSC 13.2	39121515

approvals

GOST / GOST /

Approval details



Drawings

Relay connectors - ST-REL4-KG230/21-21/AU - 2826431

Circuit diagram

