

Fuse modular terminal block - UK 10-DREHSILA 250 (6,3X32) - 3005662

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Fuse terminal block for cartridge fuse insert, cross section: 0.5 - 16 mm², AWG: 24 - 6, width: 12 mm, color: black

The illustration shows version UK
10-DREHSI (5x20)

Product Features

- ✓ Can be bridged with FBI ... fixed bridge

Key commercial data

package_quantity	50
GTIN	4017918091255

Technical data

General

Number of levels	1
Number of connections	2
Color	black
Insulating material	PA
Inflammability class according to UL 94	V2

General

Fuse	G / 6,3 x 32
Fuse type	Glass
Rated surge voltage	4 kV
Pollution degree	3
Surge voltage category	III
Insulating material group	I
Connection in acc. with standard	IEC 60947-7-3
Nominal current I _N	10 A
Nominal voltage U _N	400 V
Nominal voltage U _N	800 V (As a disconnect terminal block)
LED voltage range	110 V AC/DC ... 250 V AC/DC
LED current range	0.5 mA ... 1.1 mA
Open side panel	nein

Fuse modular terminal block - UK 10-DREHSILA 250 (6,3X32) - 3005662

Technical data

Dimensions

Width	12 mm
Length	62 mm
Height NS 35/7,5	57.2 mm
Height NS 35/15	64.7 mm
Height NS 32	62.1 mm

Connection data

Conductor cross section solid min.	0.5 mm ²
Conductor cross section solid max.	16 mm ²
Conductor cross section stranded min.	0.5 mm ²
Conductor cross section stranded max.	16 mm ²
Conductor cross section AWG/kcmil min.	20
Conductor cross section AWG/kcmil max	6
Conductor cross section stranded, with ferrule without plastic sleeve min.	0.5 mm ²
Conductor cross section stranded, with ferrule without plastic sleeve max.	10 mm ²
Conductor cross section stranded, with ferrule with plastic sleeve min.	0.5 mm ²
Conductor cross section stranded, with ferrule with plastic sleeve max.	10 mm ²
2 conductors with same cross section, solid min.	0.5 mm ²
2 conductors with same cross section, solid max.	4 mm ²
2 conductors with same cross section, stranded min.	0.5 mm ²
2 conductors with same cross section, stranded max.	4 mm ²
2 conductors with same cross section, stranded, ferrules without plastic sleeve, min.	0.5 mm ²
2 conductors with same cross section, stranded, ferrules without plastic sleeve, max.	4 mm ²
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, min.	0.5 mm ²
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, max.	10 mm ²
Cross section with insertion bridge, solid max.	10 mm ²
Cross section with insertion bridge, stranded max.	10 mm ²
Connection method	Screw connection
Stripping length	11 mm
Internal cylindrical gage	B 6
Screw thread	M4
Tightening torque, min	1.5 Nm
Tightening torque max	1.8 Nm

Fuse modular terminal block - UK 10-DREHSILA 250 (6,3X32) - 3005662

classifications

eCl@ss

eCl@ss 4.0	27141116
eCl@ss 4.1	27141116
eCl@ss 5.0	27141116
eCl@ss 5.1	27141116
eCl@ss 6.0	27141116
eCl@ss 7.0	27141116
eCl@ss 8.0	27141116

ETIM

ETIM 2.0	EC000899
ETIM 3.0	EC000899
ETIM 4.0	EC000899
ETIM 5.0	EC000899

UNSPSC

UNSPSC 6.01	30211812
UNSPSC 7.0901	39121411
UNSPSC 11	39121411
UNSPSC 12.01	39121411
UNSPSC 13.2	39121411

approvals

UL Recognized / KEMA-KEUR / GOST / CCA / IECEx CB Scheme / GOST /

Approval details


UL Recognized 	
Nominal voltage UN	300 V
Nominal current IN	20 A
mm²/AWG/kcmil	24-6

KEMA-KEUR 	
Nominal voltage UN	800 V
Nominal current IN	10 A

Fuse modular terminal block - UK 10-DREHSILA 250 (6,3X32) - 3005662

approvals

mm²/AWG/kcmil	0.5-16



IECEE CB Scheme 	
Nominal voltage UN	800 V
Nominal current IN	10 A
mm²/AWG/kcmil	0.5-16



accessories

Screwdriver tools

SZS 1,0X4,0 VDE - 1205066



Bridge

FBI 2-12 - 0200075



Fuse modular terminal block - UK 10-DREHSILA 250 (6,3X32) - 3005662

accessories

FBI 10-12 - 0203454



EB 10-12 - 3006137



Mounting rail

NS 32 PERF 2000MM - 1201002



NS 32 UNPERF 2000MM - 1201015



NS 35/ 7,5 PERF 2000MM - 0801733



Fuse modular terminal block - UK 10-DREHSILA 250 (6,3X32) - 3005662

accessories

NS 35/ 7,5 UNPERF 2000MM - 0801681



NS 35/ 7,5 WH PERF 2000MM - 1204119



NS 35/ 7,5 WH UNPERF 2000MM - 1204122



NS 35/ 7,5 AL UNPERF 2000MM - 0801704



NS 35/ 7,5 ZN PERF 2000MM - 1206421



Fuse modular terminal block - UK 10-DREHSILA 250 (6,3X32) - 3005662

accessories

NS 35/ 7,5 ZN UNPERF 2000MM - 1206434



NS 35/ 7,5 CU UNPERF 2000MM - 0801762



NS 35/ 7,5 CAP - 1206560



NS 35/15 PERF 2000MM - 1201730



NS 35/15 UNPERF 2000MM - 1201714



Fuse modular terminal block - UK 10-DREHSILA 250 (6,3X32) - 3005662

accessories

NS 35/15 WH PERF 2000MM - 0806602



NS 35/15 WH UNPERF 2000MM - 1204135



NS 35/15 AL UNPERF 2000MM - 1201756



NS 35/15 ZN PERF 2000MM - 1206599



NS 35/15 ZN UNPERF 2000MM - 1206586



Fuse modular terminal block - UK 10-DREHSILA 250 (6,3X32) - 3005662

accessories

NS 35/15 CU UNPERF 2000MM - 1201895



NS 35/15 CAP - 1206573



NS 35/15-2,3 UNPERF 2000MM - 1201798



Terminal marking

ZB 6:UNBEDRUCKT - 1051003



UC-TM 6 - 0818085



Fuse modular terminal block - UK 10-DREHSILA 250 (6,3X32) - 3005662

accessories

UCT-TM 6 - 0828736



Labeled terminal marker

ZB 6 CUS - 0824992



UC-TM 6 CUS - 0824589



UCT-TM 6 CUS - 0829602



End block

CLIPFIX 35 - 3022218



Fuse modular terminal block - UK 10-DREHSILA 250 (6,3X32) - 3005662

accessories

CLIPFIX 35-5 - 3022276



E/NS 35 N - 0800886



E/UK - 1201442



E/UK 1 - 1201413



Test socket

PSBJ 4/15/6 FARBLOS - 0303419



Fuse modular terminal block - UK 10-DREHSILA 250 (6,3X32) - 3005662

accessories

PSBJ 4/15/6 WH - 0303312



PSBJ 4/15/6 RD - 0303325



PSBJ 4/15/6 BU - 0303354



PSBJ 4/15/6 YE - 0303367



PSBJ 4/15/6 GN - 0303370



Fuse modular terminal block - UK 10-DREHSILA 250 (6,3X32) - 3005662

accessories

PSBJ 4/15/6 VT - 0303383



PSBJ 4/15/6 GY - 0303396



PSBJ 4/15/6 BK - 0303406



PSB 4/7/6 - 0303299



Drawings

© Phoenix Contact 2013 - all rights reserved
<http://www.phoenixcontact.com>