

**Repair Stick Concrete****! SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Name of product Repair Stick Concrete
Code-Nr. 105370

1.2. Relevant identified uses of the substance or mixture and uses advised against**Recommended intended purpose(s)**

2-Component Epoxy Resins

1.3. Details of the supplier of the safety data sheet**Distributor**

WEICON GmbH & Co. KG
Königsberger Str. 255, DE-48157 Münster
Phone +49(0)251 / 9322 - 0, Fax +49(0)251 / 9322 - 244
E-Mail : msds@weicon.de
Internet : www.weicon.de

Advice

Produktsicherheit / Product-Safety-Department
Phone +49(0)251 / 9322 - 0
E-mail (competent person):
msds@weicon.de

1.4. Emergency telephone number

EMERGENCY CONTACT - UK, UAE, South Africa (24h): Tel:
++44 1865 407333 (English)
TRANSPORT EMERGENCY CONTACT - UK, UAE, South
Africa (24h): Tel: ++44 1865 407333 (English)

Manufacturer

WEICON GmbH & Co. KG
Königsberger Str. 255, DE-48157 Münster

1.4. Emergency telephone number

GIFTNOTRUF/TRANSPORTNOTRUF - Deutschland (24h):
Tel: ++49 69 222 25285 (Deutsch, Englisch)

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]**

Hazard classes and Hazard categories	Hazard Statements	Classification procedure
--------------------------------------	-------------------	--------------------------

Skin Irrit. 2	H315	
Eye Irrit. 2	H319	
Skin Sens. 1	H317	
Aquatic Chronic 3	H412	

Hazard Statements

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H412	Harmful to aquatic life with long lasting effects.

2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008 [CLP/GHS]



GHS07

Signal word

Warning

Hazard Statements

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H412	Harmful to aquatic life with long lasting effects.

Precautionary Statements

P102	Keep out of reach of children.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P264	Wash hands thoroughly after handling.
P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P337 + P313	If eye irritation persists: Get medical advice/attention.
P362	Take off contaminated clothing.
P363	Wash contaminated clothing before reuse.
P501	Dispose of contents/container to hazardous or special waste collection point.

Hazardous ingredients for labelingreaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)**Special rules for supplemental label elements for certain mixtures**

Contains epoxy constituents. May produce an allergic reaction.

2.3. Other hazards**Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/ information on ingredients**3.1. Substances**

not applicable

3.2. Mixtures**Hazardous ingredients**

**Repair Stick Concrete****Hazardous ingredients (continued)**

CAS No	EC No	Name	[% weight]	Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]
25068-38-6	500-033-5	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)	1 - 10	Eye Irrit. 2, H319 / Skin Irrit. 2, H315 / Skin Sens. 1, H317 / Aquatic Chronic 2, H411
14807-96-6	238-877-9	talcum (Mg3H2(SiO3)4)	20 - 50	
26761-40-0	247-977-1	Di-Isodecyl Phthalate	1 - 5	Aquatic Acute 1, H400 / Aquatic Chronic 1, H410

REACH

CAS No	Name	REACH registration number
25068-38-6	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)	01-2119456619-26-xxxx

SECTION 4: First aid measures**4.1. Description of first aid measures****General information**

Remove contaminated soaked clothing immediately.

In case of inhalation

Remove the casualty into fresh air and keep him immobile.

In the event of symptoms refer for medical treatment.

In case of skin contact

In case of contact with skin wash off immediately with soap and water.

Consult a doctor if skin irritation persists.

In case of eye contact

After eye contact, rinse opened eye for 15 minutes under running water. Transfer to hospital for specialist examination.

In case of ingestion

Do not induce vomiting.

Call for a doctor immediately.

4.2. Most important symptoms and effects, both acute and delayed**Physician's information / possible symptoms**

Nausea

skin irritation

Physician's information / possible dangers

allergic reactions

4.3. Indication of any immediate medical attention and special treatment needed

No information available.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Foam

Dry fire-extinguishing substance

Carbon dioxide

Water spray jet

Unsuitable extinguishing media

Full water jet

Repair Stick Concrete**5.2. Special hazards arising from the substance or mixture**

Fire gas of organic material has to be classed invariably as respiratory poison.

Nitrogen oxides (NO_x)

Carbon monoxide (CO)

Carbon dioxide (CO₂)

5.3. Advice for firefighters**Special protective equipment for fire-fighters**

Fire-fighting operations, rescue and clearing work under effect of combustion and smoulder gases just may be done with breathing apparatus.

Do not inhale explosion and/or combustion gases.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures****For non-emergency personnel**

Ensure adequate ventilation.

Use personal protective clothing.

Use breathing apparatus if exposed to vapours/dust/aerosol.

6.2. Environmental precautions

Inform pollution control authorities if product gets into the sewerage systems or open waters.

Do not discharge into the drains or bodies of water..

6.3. Methods and material for containment and cleaning up

Take up mechanically and send for disposal.

6.4. Reference to other sections

Safe handling: see section 7

Disposal: see section 13

Personal protection equipment: see section 8

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

Take the usual precautions when handling with chemicals.

General protective measures

Avoid contact with eyes and skin

Do not inhale gases/vapours/aerosols.

Hygiene measures

At work do not eat, drink, smoke or take drugs.

Wash hands before breaks and after work.

Advice on protection against fire and explosion

Pay attention to general rules of internal fire prevention.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep in closed original container.

Advice on storage compatibility

Do not store with oxidizing agents.

Do not store together with acids.

**Repair Stick Concrete****Further information on storage conditions**

Protect from direct solar radiation.

Store container at cool and aired place.

Store in a dry place.

7.3. Specific end use(s)**Recommendation(s) for intended use**

See section 1.2

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Ingredients with occupational exposure limits to be monitored**

CAS No	Name	Code	[mg/m3]	[ppm]	Remark
1317-65-3	Calcium carbonate: total inhalable dust	8 hours	10		EH40/2005
1317-65-3	Calcium carbonate: respirable dust	8 hours	4		EH40/2005
26761-40-0	Diisodecyl phthalate	8 hours	5		EH40/2005
1317-65-3	Limestone: total inhalable	8 hours	10		EH40/2005
1317-65-3	Limestone: respirable	8 hours	4		EH40/2005
14807-96-6	Talc respirable dust	8 hours	1		EH40/2005
13463-67-7	Titanium dioxide: total inhalable dust	8 hours	10		EH40/2005
13463-67-7	Titanium dioxide: respirable dust	8 hours	4		EH40/2005

DNEL-/PNEC-values**DNEL worker**

CAS No	Substance name	Value	Code	Remark
25068-38-6	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)	8,33 mg/kg bw/day	DNEL long-term dermal (systemic)	
		8,33 mg/kg bw/day	DNEL long-term dermal (local)	
		12,25 mg/m3	DNEL long-term inhalative (systemic)	

PNEC

CAS No	Substance name	Value	Code	Remark
25068-38-6	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)	10 mg/l	PNEC sewage treatment plant (STP)	
		0,996 mg/kg	PNEC sediment, freshwater	
		0,006 mg/l	PNEC aquatic, freshwater	
		0,0996 mg/kg	PNEC sediment, marine water	
		0,0006 mg/l	PNEC aquatic, marine water	

Additional advice

The statutory local and national regulations have to be observed.

**Repair Stick Concrete****8.2. Exposure controls****Respiratory protection**

In case of insufficient ventilation or long-term effect use breathing apparatus.

Hand protection

Protective gloves

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.

Chemical protective gloves must be chosen carefully in view of their design and depending on the dependence on the concentration and amounts of dangerous goods used in the specific working tasks.

Eye protection

tightly fitting goggles

Other protection measures

protective clothing

Appropriate engineering controls

Sufficient ventilation and exhaustion.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties****Appearance**

pasty

Colour

whitish

Odour

hardly noticeable

Odour threshold

not determined

Important health, safety and environmental information

	Value	Temperature	at	Method	Remark
pH value	not applicable				
boiling point	> 35 °C		ca. 101 hPa		
Melting point / Freezing point	not determined				
Flash point	> 100 °C				
Vapourisation rate	not determined				
Flammable (solid)	not applicable				
Flammability (gas)	not applicable				
Ignition temperature	not determined				
Self ignition temperature	not determined				
Lower explosion limit	not determined				
Upper explosion limit	not determined				
Vapour pressure	< 500 Pa	20 °C			
Relative density	ca. 2				

**Repair Stick Concrete**

	Value	Temperature	at	Method	Remark
Vapour density	not determined				
Solubility in water					insoluble
Solubility/other	not determined				
Partition coefficient n-octanol/water (log P OW)	3,242				
Decomposition temperature	not determined				
Viscosity dynamic	not applicable				
Viscosity kinematic	not applicable				
Oxidising properties	No information available.				
Explosive properties	No information available.				
9.2. Other information	No information available.				

SECTION 10: Stability and reactivity**10.1. Reactivity**

No information available.

10.2. Chemical stability

No information available.

10.3. Possibility of hazardous reactions

Reactions with acids.

Reactions with amines.

10.4. Conditions to avoid

No information available.

10.5. Incompatible materials**Substances to avoid**

Amines

Acid

10.6. Hazardous decomposition products

Carbon monoxide and carbon dioxide.

Nitrous oxides (NOx)

Toxic gases/vapours

Thermal decomposition

Remark No decomposition if used as directed.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity/Irritation/Sensitization

	Value/Validation	Species	Method	Remark
LD50 acute oral	11400 mg/kg	rat		CAS: 25068-38-6
LD50 acute dermal	1200 mg/kg	rat		CAS: 25068-38-6
Skin irritation	irritant			
Eye irritation	irritant			
Skin sensitization	sensitizing			

Experiences made from practice

Sensitization through skin contact possible.

Irritates mucous membranes.

Irritates eyes and skin.

Additional information

The product is to be handled with the caution usual with chemicals.

Other hazardous properties may not be excluded.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicological effects

	Value	Species	Method	Validation
Fish	LC50 2 mg/l (96 h)	Oncorhynchus mykiss		CAS: 25068-38-6
Daphnia	EC50 1,8 mg/l (48 h)	Daphnia magna		CAS: 25068-38-6
Algae	EC50 220 mg/l (96 h)	Scenedesmus subspicatus		CAS: 25068-38-6

12.2. Persistence and degradability

	Elimination rate	Method of analysis	Method	Validation
Biological degradability	0 % (28 d)			not degradable

12.3. Bioaccumulative potential

Because of the n-octanol/water distribution coefficient (log K_{ow}) accumulation in organisms is possible.

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects

General regulation

Do not allow uncontrolled leakage of product into the environment.

Product is not allowed to be discharged into the ground water or aquatic environment.

Product is not allowed to be discharged into aquatic environment, drains or sewage treatment plants.



SECTION 13: Disposal considerations**13.1. Waste treatment methods****Recommendations for the product**

Remove in accordance with local official regulations.

Recommendations for packaging

Dispose of according to the local waste regulations.

Untamminated packaging may be treated as household waste.

Packaging that cannot be cleaned should be disposed of like the product.

SECTION 14: Transport information

	ADR/RID	IMDG	IATA-DGR
14.1. UN number	-	-	-
14.2. UN proper shipping name	-	-	-
14.3. Transport hazard class(es)	-	-	-
14.4. Packing group	-	-	-
14.5. Environmental hazards	-	-	-
14.6. Special precautions for user	No information available.		
14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	not applicable		
Transport/further information	No dangerous goods as defined by the transport regulations - ADR/RID, IMDG, ICAO/IATA-DGR.		

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****VOC standard**

VOC content 0 %

15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information**Recommended uses and restrictions**

National and local regulations concerning chemicals shall be observed.

For industrial use only.



Further information

Each user is responsible for the implementation of the national special regulations.

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.

Please observe the following disclaimer! --- Our safety data sheets have been compiled according to effective EU-directives, WITHOUT taking into account the special national directives concerning the handling of hazardous substances.

Indication of changes: "!" = Data changed compared with the previous version. Previous version: 8.4

- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.