

No. 1907/2006 (REACH)
Printed 12.04.2017

revision 03.08.2016 (GB) Version 8.8

Flex 310 PU

! SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Name of product Flex 310 PU Code-Nr. 133020

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended intended purpose(s)

1-Component Adhesives and Sealants, permanently elastic

1.3. Details of the supplier of the safety data sheet

Distributor WEICON GmbH & Co. KG

Königsberger Str. 255, DE-48157 Münster

Phone +49(0)251 / 9322 - 0, Fax +49(0)251 / 9322 - 244

E-Mail: msds@weicon.de Internet: www.weicon.de

Advice Produktsicherheit / Product-Safety-Department

Phone +49(0)251 / 9322 - 0 E-mail (competent person):

msds@weicon.de

1.4. Emergency telephone number

EMERGENCY CONTACT - UK, UAE, South Africa (24h): Tel:

++44 1865 407333 (English)

TRANSPORT EMERGENCY CONTACT - UK, UAE, South

Africa (24h): Tel: ++44 1865 407333 (English)

Manufacturer WEICON GmbH & Co. KG

Königsberger Str. 255, DE-48157 Münster

1.4. Emergency telephone number

GIFTNOTRUF/TRANSPORTNOTRUF - Deutschland (24h):

Tel: ++49 69 222 25285 (Deutsch, Englisch)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]

Hazard classes and Hazard

Hazard Statements Classification procedure

categories

Resp. Sens. 1 H334

Hazard Statements

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

2.2. Label elements



No. 1907/2006 (REACH)
Printed 12.04.2017

revision 03.08.2016 (GB) Version 8.8

Flex 310 PU

Labelling according to Regulation (EC) No 1272/2008 [CLP/GHS]



GHS08

Signal word

Danger

Hazard Statements

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Precautionary Statements

P102 Keep out of reach of children.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P285 In case of inadequate ventilation wear respiratory protection.

P304 + P341 IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position

comfortable for breathing.

P342 + P311 If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.

P501 Dispose of contents/container to hazardous or special waste collection point.

Hazardous ingredients for labeling

4,4-Methylendiphenyldiisocyanat, Oligomere

Special rules for supplemental label elements for certain mixtures

Contains isocyanates. May produce an allergic reaction.

2.3. Other hazards

People who suffer from skin sensitazion problems, asthma, allergies, chronic or recurring respiratory illnesses should not be deployed in any process using this preparation.

Information pertaining to special dangers for human and environment

May cause sensitization by inhalation.

Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/information on ingredients

3.1. Substances

not applicable

3.2. Mixtures

Description

Preparation of different active substances

Hazardous ingredients

CAS No	EC No	Name	[% weight]	Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]
101-68-8	202-966-0	4,4'-methylenediphenyl diisocyanate	< 0,5	Carc. 2, H351 / Acute Tox. 4, H332 / STOT RE 2, H373 / Eye Irrit. 2, H319 / STOT SE 3, H335 / Skin Irrit. 2, H315 / Resp. Sens. 1, H334 / Skin Sens. 1, H317



No. 1907/2006 (REACH)
Printed 12.04.2017

revision 03.08.2016 (GB) Version 8.8

Flex 310 PU

CAS No	EC No	Name	[% weight]	Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]
25686-28-6	500-040-3	4,4-Methylendiphenyldiisocyanat, Oligomere	< 0,2	Resp. Sens. 1, H334 / Carc. 2, H351 / STOT RE 2, H373 / Acute Tox. 4, H332 / Skin Irrit. 2, H315 / Eye Irrit. 2, H319 / Skin. Sens. 1, H317 / STOT SE 3, H335
90622-57-4	918-167-1	Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics	< 2	Flam. Liq. 3, H226 / Asp. Tox. 1, H304 / Aquatic Chronic 4, H413
1330-20-7	215-535-7	xylene	< 5	Flam. Liq. 3, H226 / STOT RE 2, H373 / Asp. Tox. 1, H304 / Acute Tox. 4, H312, H332 / Skin Irrit. 2, H315 / Eye Irrit. 2, H319 / STOT SE 3, H335
REACH				
CAS No	Name			REACH registration number
25686-28-6	4,4-Methylen	diphenyldiisocyanat, Oligomere		01-2119457013-49-xxxx
90622-57-4	Hydrocarbon	s, C11-C12, isoalkanes, < 2% aromatics		01-2119472146-39-xxxx
1330-20-7	xylene			01-2119488216-32-xxxx

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove contaminated soaked clothing immediately.

In case of inhalation

Ensure of fresh air.

In the event of symptoms refer for medical treatment.

In case of skin contact

Dab affected skin part with a cotton ball or cellulose and wash it afterwards with plenty of water and a mild cleaner. Consult a doctor if skin irritation persists.

In case of eye contact

In case of contact with eyes rinse thoroughly with plenty of water and seek medical advice.

In case of ingestion

Do not induce vomiting.

Call for a doctor immediately.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

No information available.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Alcohol-resistant foam

Dry powder

Carbon dioxide

Unsuitable extinguishing media

water



No. 1907/2006 (REACH)
Printed 12.04.2017

revision 03.08.2016 (GB) Version 8.8

Flex 310 PU

5.2. Special hazards arising from the substance or mixture

In case of fire formation of dangerous gases possible.

Nitrogen gases (NOx)

Sulfur oxide

Hydrogen chloride (HCI)

5.3. Advice for firefighters

Special protective equipment for fire-fighters

Fire-fighting operations, rescue and clearing work under effect of combustion and smoulder gases just may be done with breathing apparatus.

Do not inhale explosion and/or combustion gases.

Additional information

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

Collect contaminated firefighting water separately, must not be discharged into the drains.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Ensure adequate ventilation.

Use personal protective clothing.

Keep away sources of ignition.

Use breathing apparatus if exposed to vapours/dust/aerosol.

6.2. Environmental precautions

Do not discharge into the drains or bodies of water..

Do not discharge into the drains/surface waters/groundwater.

6.3. Methods and material for containment and cleaning up

Take up mechanically and send for disposal.

6.4. Reference to other sections

Safe handling: see section 7 Disposal: see section 13

Personal protection equipment: see section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

General protective measures

Do not inhale vapours.

Avoid contact with eyes and skin

Hygiene measures

At work do not eat, drink and smoke.

Keep away from food and drink.

Keep separated from food and feed.

Wash hands before breaks and after work.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking

Vapours can form an explosive mixture with air.



Remark

No. 1907/2006 (REACH)
Printed 12.04.2017

revision 03.08.2016 (GB) Version 8.8

Flex 310 PU

7.2. Conditions for safe storage, including any incompatibilities Requirements for storage rooms and vessels

Prevent penetration into the ground.

Advice on storage compatibility

Do not store with acids or alkalies.

Do not store together with animal feedstuffs.

Do not store together with food.

Further information on storage conditions

Keep container tightly closed and store at cool and aired place.

Protect from frost.

Protect from heat and direct solar radiation.

Store in a dry place.

Protect from heat/overheating.

7.3. Specific end use(s)

Recommendation(s) for intended use

See section 1.2

SECTION 8: Exposure controls/personal protection

Substance name

8.1. Control parameters

Ingredients with occupational exposure limits to be monitored

CAS No	Name	Code	[mg/m3]	[ppm]	Remark
1330-20-7	Xylene, o-, m-, p- or mixed isomers	8 hours	220	50	EH40/2005
		Short-term	441	100	

Code

Value

DNEL-/PNEC-values

DNEL worker

CAS No

1330-20-7	xylene	180 mg/kg	DNEL long-term dermal (systemic)	
		77 mg/m3	DNEL long-term inhalative (systemic)	
		289 mg/m3	DNEL acute inhalative (systemic)	
		289 mg/m3	DNEL acute inhalative (local)	
		289 mg/m3	DNEL acute inhalative (local)	
PNEC				
CAS No	Substance name	Value	Code	Remark
1330-20-7	xylene	2,31 mg/kg	PNEC sediment, freshwater	
		12,46 mg/kg	PNEC sediment, marine water	
		0,327 mg/l	PNEC aquatic, freshwater	
		12,46 mg/kg	PNEC sediment, freshwater	
		0,327 mg/l	PNEC aquatic, marine water	

Additional advice

The statutory local and national regulations have to be observed.

8.2. Exposure controls

Respiratory protection

If ventilation insufficient, wear respiratory protection.

Short-term: filter apparatus, filter A2/P2, otherwise environment-independent breathing apparatus.



No. 1907/2006 (REACH)
Printed 12.04.2017

revision 03.08.2016 (GB) Version 8.8

Flex 310 PU

Hand protection

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.

Chemical protective gloves must be chosen carefully in view of their design and depending on the dependence on the concentration and amounts of dangerous goods used in the specific working tasks.

Glove material specification [make/type, thickness, permeation time/life, wetting resistance]: fluorinated rubber; 0,7mm; 480min; 60min;

Eye protection

tightly fitting goggles

Other protection measures

protective clothing

Appropriate engineering controls

Sufficient ventilation and exhaustion.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

AppearanceColourOdourpastyvarioussolvent-like

Odour threshold not determined

Important health, safety and environmental information

	Value	Temperature	at	Method	Remark
pH value	not determined				
boiling point	not applicable				
melting point	not applicable				
Flash point	not applicable				
Vapourisation rate	not determined				
Flammable (solid)	not applicable				
Flammability (gas)	not applicable				
Ignition temperature	> 200 °C				
Self ignition temperature					The product is not self-igniting.
Lower explosion limit	0,4 Vol-%				
Upper explosion limit	7,6 Vol-%				
Vapour pressure	< 100 hPa	20 °C			
Relative density	1,17 g/cm3	20 °C			
Vapour density	not determined				



No. 1907/2006 (REACH) Printed 12.04.2017

revision 03.08.2016 (GB) Version 8.8

Flex 310 PU

	Value	Temperature	at	Method	Remark
Solubility in water					insoluble, reacts with water
Solubility/other	not determined				
Partition coefficient n- octanol/water (log P O/W)	not determined				
Decomposition temperature	not determined				
Viscosity dynamic	not determined				
Viscosity kinematic	not determined				
Solvent content	5,9 %				
Oxidising properties No information available.					
Explosive properties No information available.					
9.2. Other information No information available.					

SECTION 10: Stability and reactivity

10.1. Reactivity

No information available.

10.2. Chemical stability

No information available.

10.3. Possibility of hazardous reactions

Evolution of flammable gases/vapours.

Reactions with water.

Reactions with alcohols, amines, aqueous acids and alkalies.

10.4. Conditions to avoid

After contact with water:

Danger of bursting container.

10.5. Incompatible materials

Substances to avoid

Alkali (lye)

Alcohols

Amines

Acid

Water

10.6. Hazardous decomposition products

Nitrous gases

Hydrogen chloride (HCI)

Sulphurous oxides (SOx)



No. 1907/2006 (REACH)
Printed 12.04.2017

revision 03.08.2016 (GB) Version 8.8

Flex 310 PU

Thermal decomposition

Remark No decomposition if used as directed.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity/Irritation/Sensitization

	Value/Validation	Species	Method	Remark
LD50 acute oral	3523 mg/kg	rat		CAS: 1330-20-7
LD50 acute dermal	229891 mg/kg			ATE
LC50 acute inhalation	229 mg/l (4 h)			ATE
Skin irritation	low irritant effect - not necessary to label			
Eye irritation	low irritant - no labeling duty			
Skin sensitization	non-sensitizing			
Sensitization respiratory system	sensitizing			

Subacute Toxicity - Carcinogenicity

	Value	Species	Method	Validation
Mutagenicity				No experimental information on genotoxicity in vitro available.
Reproduction- Toxicity				No indications of toxic effects were observed in reproduction studies in animals.
Carcinogenicity				No indications of carcinogenic effects are available from long-term trials.

Experiences made from practice

Sensitization through inhalation possible.

Frequent persistent contact with the skin may cause skin irritation.

Additional information

The product is to be handled with the caution usual with chemicals.

Other hazardous properties may not be excluded.

The product has not been tested. The information is derived from the properties of the individual components.



No. 1907/2006 (REACH)
Printed 12.04.2017

revision 03.08.2016 (GB) Version 8.8

Flex 310 PU

SECTION 12: Ecological information

12.1. Toxicity

No information available.

12.2. Persistence and degradability

No information available.

12.3. Bioaccumulative potential

The product has not been tested. Because of the product's consistency and low solubility in water bioavailability is not likely.

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects

General regulation

Do not allow uncontrolled leakage of product into the environment.

Product is not allowed to be discharged into the ground water or aquatic environment.

Product is not allowed to be discharged into aquatic environment, drains or sewage treatment plants.

The ecotoxic effect of the product has not been tested. The information on this is given on the basis of details in the literature.

SECTION 13: Disposal considerations

13.1 Wasta treatment methods

15.1. Waste treatment met	ilous
Waste code No.	Name of waste
08 04 09*	waste adhesives and sealants containing organic solvents or other hazardous substances
08 04 10	waste adhesives and sealants other than those mentioned in 08 04 09
08 04 11*	adhesive and sealant sludges containing organic solvents or other hazardous substances
08 04 12	adhesive and sealant sludges other than those mentioned in 08 04 11
15 01 02	plastic packaging
15 01 10*	packaging containing residues of or contaminated by hazardous substances

Wastes marked with an asterisk are considered to be hazardous waste pursuant to Directive 2008/98/EC on hazardous waste.

Recommendations for the product

Remove in accordance with local official regulations.

Recommendations for packaging

Dispose of according to the local waste regulations.

General information

Assignment to a waste code number / waste identification according to the EWC is to be carried out on a sector or process-specific basis.

SECTION 14: Transport information

	ADR/RID	IMDG	IATA-DGR
14.1. UN number	-	-	-



No. 1907/2006 (REACH)
Printed 12.04.2017

revision 03.08.2016 (GB) Version 8.8

Flex 310 PU

	ADR/RID	IMDG	IATA-DGR	
14.2. UN proper shipping name	-	-	-	
14.3. Transport hazard class(es)	-	-	-	
14.4. Packing group	-	-	-	
14.5. Environmental hazard	ls -	-	-	
14.6. Special precautions for	or user			

Protect against moisture!

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

not applicable

Transport/further information

No dangerous goods as defined by the transport regulations - ADR/RID, IMDG, ICAO/IATA-DGR.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC standard

 VOC content
 5,9 %

 VOC value
 69,3 g/L

15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Recommended uses and restrictions

National and local regulations concerning chemicals shall be observed.

For industrial use only.

Further information

Each user is responsible for the implementation of the national special regulations.

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.

Please observe the following disclaimer! --- Our safety data sheets have been compiled according to effective EU-directives, WITHOUT taking into account the special national directives concerning the handling of hazardous substances.

Indication of changes: "!" = Data changed compared with the previous version. Previous version: 8.7

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312,	-?-
H332	Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.



No. 1907/2006 (REACH) Printed 12.04.2017

revision 03.08.2016 (GB) Version 8.8

Flex 310 PU

H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard).
H373	May cause damage to organs (or state all organs affected, if known) through prolonged or repeated exposure (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard).
H413	May cause long lasting harmful effects to aquatic life.