

No. 1907/2006 (REACH)
Printed 19.10.2017

revision 19.10.2017 (GB) Version 8.5

Rust Loosener

! SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Name of product Rust Loosener Code-Nr. 151502

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended intended purpose(s)

Technical Liquids

1.3. Details of the supplier of the safety data sheet

Distributor WEICON Kimya Sanayi Tic. Ltd. Sti.

Orhan Gazi Mahallesi 16. Yol Sokak No: 6, TR-34517 Esenyurt /

Istanbu

Phone +90 212 46533 65, Fax +90 212 465 33 22

E-Mail: info@weicon.com.tr Internet: www.weicon.com.tr

Advice

Phone +90 212 46533 65 Fax +90 212 465 33 22 E-mail (competent person): info@weicon.com.tr

1.4. Emergency telephone number

EMERGENCY CONTACT - UK, UAE, South Africa (24h): Tel:

++44 1865 407333 (English)

TRANSPORT EMERGENCY CONTACT - UK, UAE, South

Africa (24h): Tel: ++44 1865 407333 (English)

Manufacturer WEICON GmbH & Co. KG

Königsberger Str. 255, DE-48157 Münster

1.4. Emergency telephone number

GIFTNOTRUF/TRANSPORTNOTRUF - Deutschland (24h):

Tel: ++49 69 222 25285 (Deutsch, Englisch)

! SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

! Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]

Hazard classes and Hazard

Hazard Statements Classification procedure

categories

Asp. Tox. 1 H304 Aquatic Chronic 2 H411

Hazard Statements

H304 May be fatal if swallowed and enters airways.H411 Toxic to aquatic life with long lasting effects.



No. 1907/2006 (REACH)
Printed 19.10.2017

revision 19.10.2017 (GB) Version 8.5

Rust Loosener

2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008 [CLP/GHS]





GHS08

GHS09

! Signal word

Danger

Hazard Statements

H304 May be fatal if swallowed and enters airways.H411 Toxic to aquatic life with long lasting effects.

Precautionary Statements

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P331 Do NOT induce vomiting.

P391 Collect spillage.

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P501 Dispose of contents/container to hazardous or special waste collection point.

! Hazardous ingredients for labeling

2-(2-heptadec-8-enyl-2-imidazolin-1-yl)ethanol, (Z)-N-methyl-N-(1-oxo-9-octadecenyl)glycine, Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Supplemental Hazard information (EU)

Repeated exposure may cause skin dryness or cracking.

2.3. Other hazards

Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

! SECTION 3: Composition/ information on ingredients

3.1. Substances

not applicable

3.2. Mixtures

! Hazardous ingredients

CAS No	EC No	Name	[% weight]	Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]
95-38-5	202-414-9	2-(2-heptadec-8-enyl-2-imidazolin-1-yl) ethanol	0,25 - 0, 99	Skin Corr. 1C, H314 / Acute Tox. 4, H302 / Aquatic Acute 1, H400 M=1 / Aquatic Chronic 1, H410 M=10 / STOT RE 2, H373
	918-481-9	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics	10 < 25	Asp. Tox. 1, H304



No. 1907/2006 (REACH)
Printed 19.10.2017

revision 19.10.2017 (GB) Version 8.5

Rust Loosener

CAS No	EC No	Name	[%	Classification according to Regulation (EC)
			weight]	No 1272/2008 [CLP/GHS]
110-25-8	203-749-3	(Z)-N-methyl-N-(1-oxo-9-octadecenyl)	0,25 - 0, 99	Eye Dam. 1, H318 / Aquatic Acute 1, H400 M=1 / Acute Tox. 4. H332 / Skin Irrit. 2. H315
REACH		9.700		7,000,0 10,0 1, 11002 7 0,000 10,000
CAS No	Name			REACH registration number
95-38-5	2-(2-heptadec-8-enyl-2-imidazolin-1-yl)ethanol			01-2119777867-13-xxxx
	Hydrocarbon	s, C10-C13, n-alkanes, isoalkanes, cyclics, < 2%	aromatics	01-2119457273-39-xxxx
110-25-8	(7) NI the d	-N-(1-oxo-9-octadecenyl)glycine		01-2119488991-20-xxxx

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove contaminated soaked clothing immediately.

In case of inhalation

Ensure of fresh air.

In the event of symptoms refer for medical treatment.

In case of skin contact

In case of contact with skin wash off with water.

In case of eye contact

In case of contact with eyes rinse with plenty of water carefully. In the event of persistent symptoms seek medical treatment.

In case of ingestion

If swallowed or in case of vomiting, danger of infiltration into the lungs (danger of aspiration).

Do not induce vomiting.

Call for a doctor immediately.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treatment (Advice to doctor)

If swallowed or in the event of vomiting, risk of entering the lungs.

! SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Alcohol-resistant foam

Dry powder

Carbon dioxide

Water spray jet

! Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

In case of fire formation of dangerous gases possible.



No. 1907/2006 (REACH)
Printed 19.10.2017

revision 19.10.2017 (GB) Version 8.5

Rust Loosener

5.3. Advice for firefighters

Special protective equipment for fire-fighters

Fire-fighting operations, rescue and clearing work under effect of combustion and smoulder gases just may be done with breathing apparatus.

Additional information

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

Collect contaminated firefighting water separately, must not be discharged into the drains.

! SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Ensure adequate ventilation.

Use personal protective clothing.

6.2. Environmental precautions

Inform pollution control authorities if product gets into the sewerage systems or open waters.

Do not discharge into the drains or bodies of water..

Do not discharge into the drains/surface waters/groundwater.

6.3. Methods and material for containment and cleaning up

Take up with absorbent material (e.g. sand, kieselguhr, acid binder, general-purpose binder, sawdust).

After taking up the material dispose according to regulation.

6.4. Reference to other sections

Safe handling: see section 7 Disposal: see section 13

Personal protection equipment: see section 8

! SECTION 7: Handling and storage

7.1. Precautions for safe handling

! Advice on safe handling

Avoid formation of aerosols.

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

General protective measures

Avoid contact with eyes and skin

Do not inhale gases/vapours/aerosols.

Hygiene measures

At work do not eat, drink and smoke.

Wash hands before breaks and after work.

Advice on protection against fire and explosion

Pay attention to general rules of internal fire prevention.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep in closed original container.

Advice on storage compatibility

Do not store together with animal feedstuffs.

Do not store together with food.

Further information on storage conditions

Protect from direct solar radiation.

Keep container in a well-ventilated place

Recommended storage temperature: room temperature.



No. 1907/2006 (REACH)
Printed 19.10.2017

revision 19.10.2017 (GB) Version 8.5

Rust Loosener

7.3. Specific end use(s)

Recommendation(s) for intended use

See section 1.2

! SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Additional advice

The statutory local and national regulations have to be observed.

8.2. Exposure controls

Respiratory protection

Breathing apparatus in the event of aerosol or mist formation.

Short term: filter apparatus, combination filter A-P1

Hand protection

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.

Glove material specification [make/type, thickness, permeation time/life, wetting resistance]:: Nitrile rubber; 0,4mm; 480min; 60min.

Eye protection

tightly fitting goggles

Other protection measures

protective clothing

Appropriate engineering controls

Sufficient ventilation and exhaustion.

! SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance Colour liquid dark yellow

our Odour characteristic

Odour threshold

not determined

Important health, safety and environmental information

	Value	Temperature	at	Method	Remark	
pH value	not determined					_
boiling point	181 °C					
melting point	not determined					
Flash point	62 °C					
Vapourisation rate	not determined					
Flammable (solid)	not applicable					
Flammability (gas)	not applicable					



No. 1907/2006 (REACH) Printed 19.10.2017

revision 19.10.2017 (GB) Version 8.5

Rust Loosener

	Value	Temperature	at	Method	Remark
Ignition temperature	236 °C				
Self ignition temperature					The product is not self-igniting.
Lower explosion limit	0,7 Vol-%				
Upper explosion limit	6 Vol-%				
Vapour pressure	1 hPa	20 °C			
Relative density	0,856 g/cm3	20 °C			
Vapour density	not determined				
Solubility in water					No or low immiscibility
Solubility/other	not determined				
Partition coefficient n- octanol/water (log P O/W)	not determined				
Decomposition temperature	not determined				
Viscosity dynamic	not determined				
Viscosity kinematic	not determined				
Solvent content	16,9 %				
Solids content	0,3 %				
Oxidising properties No information available.					
Explosive properties no					
9.2. Other information No information available.					

! SECTION 10: Stability and reactivity

10.1. Reactivity

No information available.

10.2. Chemical stability

The product is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

No information available.

10.4. Conditions to avoid

Keep away from heat.



No. 1907/2006 (REACH) Printed 19.10.2017

revision 19.10.2017 (GB) Version 8.5

Rust Loosener

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

No hazardous decomposition products known.

Thermal decomposition

Remark No decomposition if used as directed.

! SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity/Irritation/Sensitization

	Value/Validation	Species	Method	Remark
LD50 acute oral	> 5000 mg/kg	rat		EG: 918-481-9
LD50 acute dermal	> 5000 mg/kg	rabbit		EG: 918-481-9
LC50 acute inhalation	> 4951 mg/l (4 h)	rat		EG: 918-481-9
Skin irritation	non-irritant			
Eye irritation	low irritant - no labeling duty			
Skin sensitization	non-sensitizing			

Subacute Toxicity - Carcinogenicity

	Value	Species	Method	Validation
Mutagenicity				No experimental information on genotoxicity in vitro available.
Reproduction- Toxicity				No indications of toxic effects were observed in reproduction studies in animals.
Carcinogenicity				No indications of carcinogenic effects are available from long-term trials.

! Aspiration hazard

May be fatal if swallowed and enters airways.

Experiences made from practice

Often and long skin contact may cause degreasing and desiccation of the skin which may caus skin irritation.

! Additional information

The product is to be handled with the caution usual with chemicals.

Other hazardous properties may not be excluded.



No. 1907/2006 (REACH)
Printed 19.10.2017

revision 19.10.2017 (GB) Version 8.5

Rust Loosener

! SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicological effects

	Value	Species	Method	Validation
Fish	LL0 1000 mg/l (96 h)	Oncorhynchus mykiss		EG: 918-481-9
Daphnia	EL0 1000 mg/l (48 h)	Daphnia magna		EG: 918-481-9
Algae	EL0 1000 mg/l (72 h)	Pseudokirchneriella subcapitata		EG: 918-481-9

12.2. Persistence and degradability

No information available.

12.3. Bioaccumulative potential

No information available.

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects

! General regulation

Toxic to aquatic life, fishes and plankton.

Toxic to aquatic life with long lasting effects.

Do not allow uncontrolled leakage of product into the environment.

Product is not allowed to be discharged into aquatic environment, drains or sewage treatment plants.

! SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste code No.

Name of waste

13 02 05*

mineral-based non-chlorinated engine, gear and lubricating oils

Wastes marked with an asterisk are considered to be hazardous waste pursuant to Directive 2008/98/EC on hazardous waste.

Recommendations for the product

Remove in accordance with local official regulations.

Recommendations for packaging

Dispose of according to the local waste regulations.

! General information

Assignment to a waste code number / waste identification according to the EWC is to be carried out on a sector or process-specific basis.

SECTION 14: Transport information

	ADR/RID	IMDG	IATA-DGR	
14.1. UN number	-	-	-	



No. 1907/2006 (REACH)
Printed 19.10.2017

revision 19.10.2017 (GB) Version 8.5

Rust Loosener

	ADR/RID	IMDG	IATA-DGR
14.2. UN proper shipping name	-	-	-
14.3. Transport hazard class(es)	-	-	-
14.4. Packing group	-	-	-
14.5. Environmental hazards	-	-	-

14.6. Special precautions for user

No information available.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code not applicable

Transport/further information

No dangerous goods as defined by the transport regulations - ADR/RID, IMDG, ICAO/IATA-DGR.

! SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC standard

VOC content 16,9 % **VOC value** 144,7 g/L

15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

! SECTION 16: Other information

! Recommended uses and restrictions

National and local regulations concerning chemicals shall be observed.

For industrial use only.

Further information

Each user is responsible for the implementation of the national special regulations.

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.

Please observe the following disclaimer! --- Our safety data sheets have been compiled according to effective EU-directives, WITHOUT taking into account the special national directives concerning the handling of hazardous substances.

Indication of changes: "!" = Data changed compared with the previous version. Previous version: 8.4

H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H332	Harmful if inhaled.
H373	May cause damage to organs (or state all organs affected, if known) through prolonged or repeated exposure (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard).
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.