

! SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier	
Name of product	WEICONLOCK AN 306-10 Code-Nr. 306100
 1.2. Relevant identified uses of the substance Recommended intended purpose(s) 1-Component Adhesives and Sealants, anaerobi 	-
1.3. Details of the supplier of the safety data s	sheet
Distributor	WEICON GmbH & Co. KG Königsberger Str. 255, DE-48157 Münster Phone +49(0)251 / 9322 - 0, Fax +49(0)251 / 9322 - 244 E-Mail : msds@weicon.de Internet : www.weicon.de
Advice	Produktsicherheit / Product-Safety-Department Phone +49(0)251 / 9322 - 0 E-mail (competent person): msds@weicon.de
1.4. Emergency telephone number	
	EMERGENCY CONTACT - UK, UAE, South Africa (24h): Tel: ++44 1865 407333 (English) TRANSPORT EMERGENCY CONTACT - UK, UAE, South Africa (24h): Tel: ++44 1865 407333 (English)
Manufacturer	WEICON GmbH & Co. KG Königsberger Str. 255, DE-48157 Münster
1.4. Emergency telephone number	
	GIFTNOTRUF/TRANSPORTNOTRUF - Deutschland (24h): Tel: ++49 69 222 25285 (Deutsch, Englisch)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]

Hazard classes an categories	d Hazard Hazard S	Statements	Classification procedure
Skin Irrit. 2	H315		
Eye Irrit. 2	H319		
Skin Sens. 1	H317		
STOT SE 3	H335		
Hazard Statemen	ts		
H315	Causes skin irritation.		
H317	May cause an allergic	skin reaction	
H319	Causes serious eve irri		

11010	Oddoco ochodo cyc initation.
H335	May cause respiratory irritation.



2.2. Label elements Labelling according to Regulation (EC) No 1272/2008 [CLP/GHS]



GHS07

Signal word Warning

Hazard Statements

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.

Precautionary Statements

P102	Keep out of reach of children.
P261 P264 P271 P272 P280	Avoid breathing dust/fume/gas/mist/vapours/spray. Wash hands thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection.
P302 + P352 P304 + P340 P305 + P351 + P338 P312 P332 + P313 P333 + P313 P337 + P313 P362 P363	 IF ON SKIN: Wash with plenty of soap and water. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a POISON CENTER or doctor/physician if you feel unwell. If skin irritation occurs: Get medical advice/attention. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing. Wash contaminated clothing before reuse.
P403 + P233 P405	Store in a well-ventilated place. Keep container tightly closed. Store locked up.
P501	Dispose of contents/container to hazardous or special waste collection point.

Hazardous ingredients for labeling

2-hydroxyethyl methacrylate

2.3. Other hazards

Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/ information on ingredients

3.1. Substances not applicable

3.2. Mixtures Description Anaerobic adhesive / sealant



Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) Printed 12.04.2017

revision 03.08.2016 (GB) Version 8.4

WEICONLOCK AN 306-10

CAS No	EC No	Name	[% weight]	Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]
79-10-7	201-177-9	acrylic acid	1 - 3	Flam. Liq. 3, H226 / Acute Tox. 4, H332 / Acute Tox. 4, H312 / Acute Tox. 4, H302 / Skin Corr. 1A, H314 / Aquatic Acute 1, H400
868-77-9	212-782-2	2-hydroxyethyl methacrylate	1 - 5	Eye Irrit. 2, H319 / Skin Irrit. 2, H315 / Skin Sens. 1, H317
80-15-9	201-254-7	cumene hydroperoxide	0,1 < 1	Org. Perox. E, H242 / Acute Tox. 3, H331 / Acute Tox. 4, H312 / Acute Tox. 4, H302 / STOT RE 2, H373 / Skin Corr. 1B, H314 / Aquatic Chronic 2, H411
40220-08-4	254-843-6	(2,4,6-trioxo-1,3,5-triazine-1,3,5(2H,4H,6H)- triyl)tri-2,1-ethanediyl triacrylate	10 - 30	Skin Irrit. 2, H315 / Eye Irrit. 2, H319

SECTION 4: First aid measures

4.1. Description of first aid measures

General information Remove contaminated soaked clothing immediately.

In case of inhalation

Ensure of fresh air. In the event of symptoms refer for medical treatment.

In case of skin contact

In case of contact with skin wash off immediately with soap and water. Consult a doctor if skin irritation persists.

In case of eye contact

In case of contact with eyes rinse thoroughly with plenty of water and seek medical advice.

In case of ingestion

Do not induce vomiting. Refer to medical treatment. If swallowed give water to drink.

4.2. Most important symptoms and effects, both acute and delayed Physician's information / possible symptoms Allergic symptoms Confusion skin irritation

Physician's information / possible dangers Causes serious eye damage.

4.3. Indication of any immediate medical attention and special treatment needed No information available.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Foam Dry fire-extinguishing substance Carbon dioxide sand Water spray jet



Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

In case of fire formation of dangerous gases possible. Carbon monoxide (CO) Carbon dioxide (CO2)

5.3. Advice for firefighters

Special protective equipment for fire-fighters

Fire-fighting operations, rescue and clearing work under effect of combustion and smoulder gases just may be done with breathing apparatus. Do not inhale explosion and/or combustion gases.

Additional information

Cool endangered containers with water spray jet.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel Ensure adequate ventilation. Use personal protective clothing. Keep away sources of ignition. Use breathing apparatus if exposed to vapours/dust/aerosol.

6.2. Environmental precautions

Do not discharge into the drains/surface waters/groundwater. Do not discharge into the subsoil/soil.

6.3. Methods and material for containment and cleaning up

Take up with absorbent material (e.g. sand, kieselguhr, acid binder, general-purpose binder, sawdust). After taking up the material dispose according to regulation.

6.4. Reference to other sections

Safe handling: see section 7 Disposal: see section 13 Personal protection equipment: see section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

General protective measures

Do not inhale vapours. Avoid contact with eyes and skin

Hygiene measures

At work do not eat, drink and smoke. Remove soiled or soaked clothing immediately. Wash hands before breaks and after work.

Advice on protection against fire and explosion

Pay attention to general rules of internal fire prevention.



7.2. Conditions for safe storage, including any incompatibilities Requirements for storage rooms and vessels

Keep only in original container.

Advice on storage compatibility

Do not store together with animal feedstuffs. Do not store together with food. Do not store together with oxidizing agents. Do not store together with reducing agents. Do not store together with metals.

Further information on storage conditions

Store at +5 till +25 °C. Protect from heat and direct solar radiation. Store container at cool and aired place.

7.3. Specific end use(s)

Recommendation(s) for intended use See section 1.2

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Additional advice

The statutory local and national regulations have to be observed.

8.2. Exposure controls

Respiratory protection

In case of insufficient ventilation or long-term effect use breathing apparatus. Breathing apparatus in the event of aerosol or mist formation.

Hand protection

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.

Chemical protective gloves must be chosen carefully in view of their design and depending on the dependence on the concentration and amounts of dangerous goods used in the specific working tasks.

Glove material specification [make/type, thickness, permeation time/life, wetting resistance]: fluorinated rubber; 0,7mm; 480min; 60min;

Eye protection

tightly fitting goggles

Other protection measures protective clothing

Appropriate engineering controls Sufficient ventilation and exhaustion.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties		
Appearance	Colour	
liquid	green	
Odour threshold		

Odour hardly noticeable



not determined

Important health, safety and environmental information

	Value	Temperature	at	Method	Remark
pH value	not determined				
boiling point	not determined				
melting point	not determined				
Flash point	> 100 °C				
Vapourisation rate	not determined				
Flammable (solid)	not determined				
Flammability (gas)	not determined				
Ignition temperature	not determined				
Self ignition temperature	not determined				
Lower explosion limit	not determined				
Upper explosion limit	not determined				
Vapour pressure	not determined				
Relative density	ca. 1,1 g/ml				
Vapour density	not determined				
Solubility in water		20 °C			No or low immiscibility
Solubility/other			acetone		teilweise mischbar
Partition coefficient n- octanol/water (log P O/W)	not determined				
Decomposition temperature	not determined				
Viscosity	ca. 750 mPa*s				
Oxidising properties No information available.					
Explosive properties No information available.					
9.2. Other information No information available.					



SECTION 10: Stability and reactivity

10.1. Reactivity No information available.

10.2. Chemical stability

No information available.

10.3. Possibility of hazardous reactions Reactions with strong oxidising agents.

Reactions with reducing agents. Reactions with Metals.

10.4. Conditions to avoid

Metal, Metal-Salts Keep away from heat.

10.5. Incompatible materials

Substances to avoid Oxidising agent, strong Reducing agent, strong Metal, Metal-Salts

10.6. Hazardous decomposition products

Gases/vapours, toxic Carbon monoxide and carbon dioxide.

Thermal decomposition

Remark No decomposition if used as directed.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity/Irritation/Sensitization

	Value/Validation	Species	Method	Remark
Skin irritation	irritant			
Eye irritation	irritant - risk of strong eye injuries			
Skin sensitization	sensitizing			
Experiences made fr	om practice			

Experiences made from practice Sensitization through skin contact possible. Irritates eyes and skin.

Additional information

The product is to be handled with the caution usual with chemicals.

Other hazardous properties may not be excluded.

The product has not been tested. The information is derived from products of similar composition.



SECTION 12: Ecological information

12.1. Toxicity

No information available.

12.2. Persistence and degradability

No information available.

12.3. Bioaccumulative potential

No information available.

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects

General regulation

Harmful to aquatic life with long lasting effects. Do not allow uncontrolled leakage of product into the environment. Product is not allowed to be discharged into aquatic environment. The ecotoxic effect of the product has not been tested. The information on this was derived from products of similar structure or composition.

SECTION 13: Disposal considerations

13.1. Waste treatment methods	
Waste code No.	Name of waste
08 04 09*	waste adhesives and sealants containing organic solvents or other hazardous
	substances

Wastes marked with an asterisk are considered to be hazardous waste pursuant to Directive 2008/98/EC on hazardous waste.

Recommendations for the product

Remove in accordance with local official regulations.

Recommendations for packaging

Dispose of according to the local waste regulations.

SECTION 14: Transport information

	ADR/RID	IMDG	IATA-DGR
14.1. UN number	-	-	-
14.2. UN proper shipping name	-	-	-
14.3. Transport hazard class(es)	-	-	-
14.4. Packing group	-	-	-
14.5. Environmental hazards	-	-	-



14.6. Special precautions for user

No information available.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

not applicable

Transport/further information

No dangerous goods as defined by the transport regulations - ADR/RID, IMDG, ICAO/IATA-DGR.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC standard	
VOC content	ca.5 %
VOC value	40,5 g/L

15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Recommended uses and restrictions

National and local regulations concerning chemicals shall be observed. For industrial use only.

Further information

Each user is responsible for the implementation of the national special regulations.

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product. Please observe the following disclaimer! --- Our safety data sheets have been compiled according to effective EU-directives, WITHOUT taking into account the special national directives concerning the handling of hazardous substances.

Indication of changes: "!" = Data changed compared with the previous version. Previous version: 8.3

- H226 Flammable liquid and vapour.
- H242 Heating may cause a fire.
- H302 Harmful if swallowed.
- H312 Harmful in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H331 Toxic if inhaled.
- H332 Harmful if inhaled.
- H373 May cause damage to organs (or state all organs affected, if known) through prolonged or repeated exposure (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard).
- H400 Very toxic to aquatic life.
- H411 Toxic to aquatic life with long lasting effects.